



MODEL KONTAKT 155/K GREEN LINE

BENEFIT AND FUNCTIONAL CHARACTERISTICS
OF LINDR CONTACT DISPENSING SYSTEMS:

CZECH UP YOUR BEER COOLING AND DISPENSING SYSTEMS

Dispensing systems from the KONTAKT 155 GREEN LINE series are designed for professional cooling, dispensing and serving of perfectly chilled beer and other beverages on commercial and non-commercial events and festivals, with ability to dispense up to 2 beverages at once thanks to two-tap design. Their size and built-in air system open up new possibilities even in professional environments.

| AIR COMPRESSOR

The KONTAKT 155/K cooler is fitted with a unique system of a built-in, silent, high-quality air compressor fitted with a noise dampener and a molecule filter for incoming air. The air system is fully automated and set to an operating pressure of 2.8 - 3.2 bar.



GREEN LINE – LINDR GREEN LINE technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption.**

LINDR THERMAL BLOCK – the compressor cooling unit uses the power input for direct transfer to chilling, which guarantees minimum energy usage. Perfectly chilled beer is ready within a few minutes after switching the cooler on.

LINDR COOLING TECHNOLOGY – always more powerful than its electric input power.

STAINLESS CONSTRUCTION – The entire body and the coil of the cooler are made of stainless steel. The materials used meet the strictest hygienic standards and guarantee long service life of the cooler.

PERFORMANCE, QUALITY, SIZE – the best performance/ quality/ size ratio.

VERSATILITY – Can also be used with a bar dispense tower.

✓ **GREEN LINE** – all models in the KONTAKT 155 series come in full GREEN LINE design.

✓ **IMPROVED PERFORMANCE** – KONTAKT 155 series dispensing systems boast a continuous output of 120-160 l/h, allowing you to serve 240-320 perfectly chilled drinks an hour.

✓ **KEG PRESSURISATION** – MODELS KONTAKT 155/K are equipped with a unique system of a built-in, silent, more powerful high-quality air compressor fitted with a noise dampener, a molecule filter for incoming air and automatic operating pressure setting.

✓ **SIMPLE OPERATION** – the KONTAKT 155/R cooler is equipped with a built-in two-level CO₂ reduction valve with pressure gauges and is capable of regulating two separate operating pressures for connection to a CO₂ cylinder.

✓ **COMFORTABLY PORTABLE** – ease and safety of handling is still maintained thanks to the system's size and two handles located on top.

✓ **EQUIPMENT** – thermostat allowing smooth and precise regulation of beverage temperature, dispensing tap, tap wrench, drip tray and speedfit fittings for easy connection.

TECHNICAL PARAMETERS



AVAILABLE CUSTOM MODIFICATION OPTIONS

CHOICE OF TAPS

YES


BEER/ AIR STAINLESS STEEL SCREWING - 6 5/8"

POWER CABLE PLUG

Note
Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage.
Other custom modifications are also available (contact us).

PRODUCT MODEL

KONTAKT 155/K GL

COOLING POWER OF THE COMPRESSOR (HP)	3/4
COOLING POWER OF THE COMPRESSOR (W)	1550
MAXIMUM COOLING CAPACITY TO 0°C / TK 45°C (L/HOUR)	160
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	120
THERMAL GRADIENT ΔT (°C)	10
AIR COMPRESSOR (BAR)	YES, AUTOMATIC 2,8-3,2
NUMBER OF TAPS (PCS)	2
NUMBER/ LENGHT OF COOLING COILS (M)	2/ 26,0
POWER (W)	966
AMPERAGE (A)	4,20
NET WEIGHT (KG)	42,0
TYPE OF REFRIGERANT	 R290
VOLTAGE	220-240V 50HZ~1
CONNECTION BEER/ AIR - SPEEDFIT FITTINGS	3/8, 5/16

