

Energy Saving-AUTO HEAT OFF

LATTE'



Photo Laminator A4size・A3size

Protects, Preserves and Enhances your documents

Temperature Control

easy setting

Reverse Switch

prevents paper jam

Film Thickness

from 80 to 150mic.

Auto Heat Off

for energy saving

Designed specially for home users and small office users. Equipped with safety measures such as Reverse Switch and Auto Heat Off.



Document



ID card



Photograph



Menu



Price card

Lamipacker® LPD3221

From business card size
up to A3
(Max laminating width 320mm)



Lamipacker® LPD2321

From business card size
up to A4
(Max laminating width 230mm)



Simple Operation





A4size・A3size

Energy Saving-AUTO HEAT OFF

Lamipacker®

LPD2321
LPD3221

LATTE'



Temperature Control
easy setting



Reverse Switch
prevents paper jam



Film Thickness
from 80 to 150mic.



for energy
saving



Laminating Speed
0.36m/min



Warm up Time
6-10min



Reverse function will prevent paper jams

Auto Heat Off will serve you as an energy saving, and safe operation.

Features

- Operation is simple: Suitable for use at home, office, or any other place you like.
- Temperature setting is easy: Just choose the right setting for your lamination.
- Reverse switch enables you to prevent paper jams.
- Auto Heat Off: ideal for saving energy. After continuous running of one hour, the heating up will stop automatically.
- Laminating speed: 360mm/min. Laminates an A4 sheet in 50 sec.
- Warms up and gets ready in 6 minutes.
- Detachable wide tray at the rear will enhance the lamination outcome.

Specifications

Model	Lamipacker LATTE' A4	Lamipacker LATTE' A3
Item No.	LPD2321	LPD3221
Max.Laminating Width	230mm(A4)	320mm(A3)
Max.Laminating Thickness	0.6mm(including film thickness)	
Laminating Speed	360mm/min.(50Hz) 430mm/min.(60Hz)	
Laminatable Film Thicknesses	80-150 microns	
Warm-Up Time	Approx.6-10 min.	
Heating Method	2 roller / external heating system	
Power Source / Power Consumption	AC 220-240V(50/60Hz) 300W	AC 220-240V(50/60Hz) 480W
Dimensions / Weight(excl. Rear Tray)	375(W)x162(D)x106(H) / 2.0kg	465(W)x182(D)x108(H) / 3.1kg
Attachments	Rear Tray, Cleaning Paper, Users Guide	
Remarkable Function	Reverse Function / Auto Heat Off	
Package Size / Weight	406(W)x132(D)x186(H) / 2.4kg	496(W)x134(D)x207(H) / 3.7kg
Carton Size / Weight	430(W)x410(D)x310(H) / 4 units / 10.6kg	515(W)x450(D)x190(H) / 2 units / 8.4kg

*Warm-up time depends on room temperature.
*Specification may be modified without prior notice.

Our patent product

Effects

- As a result of lamination, the efficiency of durability and water resistance is improved and the laminated object is protected from scratches, stains and water.
- The color printing is not only more durable but also more vivid as lamination process makes surface of the laminated object flat and smooth.
- The laminated objects, such as documents or printed materials, are completely sealed and protected from oxidization of ink, color fade-out or changing colors.
- By choosing film from various sizes and thicknesses, the lamination possibilities will be widened at home or in the office.
- It is also possible to obtain the UV cut effect.

Lamination Film

It is recommended to use our genuine FUJIPLA "CP-Leaf". Use of other films may cause trouble (e.g. jamming etc.)

⚠ Safety Warning

- Read the instruction manual thoroughly before operation to avoid danger and failure of the lamination.
- In the cases listed below, please stop operation, unplug and contact your FUJIPLA dealer immediately.
 - The power supply cord or plug gets unusually hot.
 - Strange smell or smoke comes out.
 - Water or foreign objects get inside the machine.
- Warning and caution signs are omitted in the photographs run on this catalogue.
- Specification and appearance of the product may change for improvement reasons without notice.
- Maintenance parts for maintenance service are available for a minimum of 5 years after cessation of the manufacture of product.

This catalogue is valid as of February 2010.

Contact:

FUJIPLA Inc.
TOKYO, JAPAN

<http://www.fujipla-japan.com>