

KS-11550

Cross Cut 5x40~120
Cross Cut 10x40~120
Cross Cut 15x40~120
Cross Cut 20x40~120



Shredder Features

Super Cleaning Cutter / Power Saving function / New designed 'Easy Display' / Diagnosis Reader for Service

Special hardened Cutter and metal Gears & Guides / Double Thermal Protect (Motor & PCB)

Impact-resistant Plastic Shred Bin or transparent plastic Vinyl Bag /

Casters with Stopper for easy installation

Auto Start / Stop controlled by photo cell and PCB

Auto Stop when door is open / Sensor Recovery / Auto Cleaning for 1min.

▪ FEED OPENING in mm	550
▪ VOLTAGE / FREQUENCY	3Phase / 220V, 380V / 50, 60Hz
▪ DIMENSION (WxDxH in mm)	1200 x 2100 x 1620
▪ WEIGHT (kg)	1430
▪ BIN VOLUME (Liter)	(Waste Bin) 430
▪ APPLICABLE FOR PAPER and	Paper, CD, DISK, TAPES, BINDER and etc

CUTTING TYPE	Cross Cut
SHRED SIZE in mm	5 x 40~120
SECURITY LEVEL (DIN 32757-1)	Lv. 2
SHRED CAPACITY (Sheets 70gsm)	500
CUTTING SPEED (m/Min)	8
POWER CONSUMPTION (Watt)	8360

CUTTING TYPE	Cross Cut
SHRED SIZE in mm	10 x 40~120
SECURITY LEVEL (DIN 32757-1)	Lv. 2
SHRED CAPACITY (Sheets 70gsm)	500
CUTTING SPEED (m/Min)	10
POWER CONSUMPTION (Watt)	8360


CUTTING TYPE	Cross Cut
SHRED SIZE in mm	15 x 40~120
SECURITY LEVEL (DIN 32757-1)	Lv. 2
SHRED CAPACITY (Sheets 70gsm)	500
CUTTING SPEED (m/Min)	3.5
POWER CONSUMPTION (Watt)	8360

CUTTING TYPE	Cross Cut
SHRED SIZE in mm	20 x 40~120
SECURITY LEVEL (DIN 32757-1)	Lv. 2
SHRED CAPACITY (Sheets 70gsm)	500
CUTTING SPEED (m/Min)	12
POWER CONSUMPTION (Watt)	8360



► Super Cleaning Cutter

- Keep remaining shred capacity without oiling for a long time
- Cutter Coefficient of friction is decreased.
- Special Heat Treatment for Cutter with Kostal owned technology



► Special Treated & Cutting Head

- Special Heat Treatment for Cutter, Guide, Ring
- Metal Gears for Shredder Durability
- Commercial-Grade All-Metal Gearing Driving the Cutting Heads vs. Typical Plastic Gearing



► Geared Motor & TP function

- Powerful & Durable AC Geared Motors Far Outlast the Competition
- Motor TP (Thermal Protector) - inner side of Motor
- TP controlled by Main PCB Sensor
- All Shredder models included TP function.



► Diagnosis Reader

- Count Motor operating time / Rev. / Auto Rev. / Sensor detecting / Waste full
- Check Valuable data for After Service (AS) & Before Service (BS)