



Pannello LCD
LCD panel



Particolari soffieria
Blower vision



Cambio rapido utensile
Change tool

Specifiche tecniche

Formato min/max cm 8x10 / cm 50x70 (con prolunga cm 50x85 optional)
Grammatura da 80 a 400 gr/mq
Programmazione 20 programmi (20 operazioni per programma)
Distanza min. cordonature mm 0,1
Velocità in A4 6.500 fogli/h (con 1 cord.)
Alimentazione elettrica 230 Volt 50 Hz monofase
Potenza richiesta 2 Kw
Peso netto 180 Kg
Dimensioni 150x75x120 cm
Opzioni kit perforante 2/1 - 3/1 - 4/1; kit cordonante standard

Size Min / Max cm 8x10 / cm 50x70 (with optional extension 50x85 cm)
Sheet weight 80 to 400 g.s.m.
Programs 20 programs with 20 operations for each program
Min. distance creasings mm 0,1
Production A4 with 1 crease 6,500 sheets per hour
Power supply 230 Volts 50 Hz single phase
Power requirement 2 Kw
Net weight 180 Kg
Size 150x75x120 cm
Optionals perforating kit 2/1 - 3/1 - 4/1; standard creasing kit

Technical specifications

DG LINE 6500

IDEALE PER LA STAMPA DIGITALE

Macchina cordonatrice perforatrice automatica con alimentazione ad aspirazione **bassa pila non stop**. La PIT STOP DG LINE 6500 è indicata per le aziende che offrono il "print on demand" e che richiedono alte qualità di lavorazione su stampati "digitali", semplicità e rapidità di avviamento. Il formato è adeguato al digitale ed anche alle copertine dei libri (book on demand). Con prolunga 50x85, senza prolunga 50x70. La PIT STOP DG LINE 6500 ha la possibilità di inserire il kit di perforazione standard (optional) programmandolo direttamente sulla macchina.

IDEAL FOR PRINT ON DEMAND

Automatic perforating/creasing machine with a **low pile feeder**. The PIT STOP DG LINE 6500 is ideal for the companies who offer "print on demand" and who expect high quality products from digitally printed stock with fast and simple operation. The format is adapted to digital and also book covers (books on demand) with extension 50x85, without extension (standard 50x70). It is also possible on the PIT STOP DG LINE 6500 to attach a standard perforating kit (optional extra) which can be programmed directly from the display.