

KS-11410

Cross Cut 5x40
Strip Cut 4~12



Shredder Features

Super Cleaning Cutter / Power Saving function / New designed 'Easy Display' / Diagnosis Reader for Service

Special hardened Cutter and metal Gears & Guides / Double Thermal Protect (Motor & PCB)

Impact-resistant Plastic Shred Bin or transparent plastic Vinyl Bag /

Casters with Stopper for easy installation

Auto Start / Stop controlled by photo cell and PCB

Auto Stop when door is open / Sensor Recovery / Auto Cleaning for 1min.


- FEED OPENING in mm 410
- VOLTAGE / FREQUENCY 110~230V / 50, 60Hz
- DIMENSION (WxDxH in mm) 720 x 1330 x 1220
- WEIGHT (kg) 457
- BIN VOLUME (Liter) (Waste Bin) 300
- APPLICABLE FOR PAPER and Paper, CD, DISK, TAPES, BINDER and etc

CUTTING TYPE	Cross Cut
SHRED SIZE in mm	5 x 40
SECURITY LEVEL (DIN 32757-1)	Lv. 3
SHRED CAPACITY (Sheets 70gsm)	70~80
CUTTING SPEED (m/Min)	12
POWER CONSUMPTION (Watt)	3784
CUTTING TYPE	Strip Cut
SHRED SIZE in mm	4~12
SECURITY LEVEL (DIN 32757-1)	Lv. 1
SHRED CAPACITY (Sheets 70gsm)	100~110
CUTTING SPEED (m/Min)	15
POWER CONSUMPTION (Watt)	2640



► Super Cleaning Cutter

- Keep remaining shred capacity without oiling for a long time
- Cutter Coefficient of friction is decreased.
- Special Heat Treatment for Cutter with Kostal owned technology



► Special Treated & Cutting Head

- Special Heat Treatment for Cutter, Guide, Ring
- Metal Gears for Shredder Durability
- Commercial-Grade All-Metal Gearing Driving the Cutting Heads vs. Typical Plastic Gearing



► Geared Motor & TP function

- Powerful & Durable AC Geared Motors Far Outlast the Competition
- Motor TP (Thermal Protector) - inner side of Motor
- TP controlled by Main PCB Sensor
- All Shredder models included TP function.



► Diagnosis Reader

- Count Motor operating time / Rev. / Auto Rev. / Sensor detecting / Waste full
- Check Valuable data for After Service (AS) & Before Service (BS)