


LED Spotlight—MR16 Series



Benefits

- 3*1w High power led light
- High heat-sink performance
- The optics lens design solution
- No UV or IR radiation
- No strobe flashing
- Tremendous energy saving
- With Remote Controller

Fundamental

Item	specification	Item	specification
Part No.	TT-1W03M16-XX-R	Housing Material	Aluminium Alloy
Base Type	MR16	Total Size	φ50mm*H51mm
Beam Angle	30°	Weight	65 g
LED source	Epistar Chip	Packing	1pcs/white box,100pcs/carton
Safety Certificate	CE/RoHS	Carton Size	32.0*32.0*30.0cm
Warranty	2 years	N.W./G.W.	6.8kg/8.8kg
Life-span	50,000Hours		

Construction

Item	specification	Item	specification
Input Voltage	AC/DC 12V	Luminous Flux per 1-watt	80~90 lm (cool white)
Work Frequency	50~60Hz	Luminous Flux per lamp	190 lm (6200k)
LED QTY	3 pcs	Working Temperature	-20~+50℃
Power	3 ×1w	Color Rendering Index	75~85
Color Temperature	2800~7000K	Brightness attenuation	Less than 3% per 1KH
Light Color	Warm white(2800~3500k),Natural white(3500~5000k),cool white(5000~7000k)		

Remote Controller Feature

Function: Dimmer(Brightness can be selected 10%~100%)

Flash(Speed frequency can be selected 1/2 seconds to 2 seconds)

Distance(less than 7m)

Remark

- Mark sure the power supply is adapted to the right voltage before using;
- Please insure that the switch is off before connect the power supply;
- Please don't touch the metal body and stare at the light source directly while lighting;
- Keep water away while using outdoor.

Application

•Wide ranging applications,for instance:Interior Decotation,some place where requiring special lighting effects(Say:Home cinema,Karaoke Box Centers,Stage,Bar and leisure centers).

