



Specifikationer ILL LED/RGB-kontroller med R/F Fjärrkontroll

Anslutningsspänning: 12VDC

Antal kanaler: 3st R, G och B

Belastning: max 4A per kanal

Omgivningstemperatur: -20 - 60°

Inkoppling: Gemensam anod

Storlek: 95 x 65 x 25mm

Knappfunktioner

A - Växla mellan program och statiska färger

B - Öka hastighet eller Dimma upp

C - Minska hastighet eller Dimma ned

D - On / Off

Item	Patterns	B Key	C Key	D Key
A Key 1 time	Gradual changing	Speed up	Slow down	Turn on/off
A Key 2 time	Jumping changing	Speed up	Slow down	Turn on/off
A Key 3 time	Static Red	Dimmer down	Dimmer up	Turn on/off
A Key 4 time	Static Green	Dimmer down	Dimmer up	Turn on/off
A Key 5 time	Static Blue	Dimmer down	Dimmer up	Turn on/off
A Key 6 time	Static Yellow	Dimmer down	Dimmer up	Turn on/off
A Key 7 time	Static Cyan	Dimmer down	Dimmer up	Turn on/off
A Key 8 time	Static Purple	Dimmer down	Dimmer up	Turn on/off
A Key 9 time	Static White	Dimmer down	Dimmer up	Turn on/off
A Key 10 time	Gliding	Speed up	Slow down	Turn on/off
A Key 11 time	Chase	Speed up	Slow down	Turn on/off
A Key 12 time	Flash frequently	Speed up	Slow down	Turn on/off