

Specification of Ultra-thin linear LED wall washer

Product Introduction:

SUNRICE ultra-thin LED wall washer adopts high power 1W/3W LED as lighting source , single color and RGB full color available, controlled by simple DMX512 controller or regular 4-wire, 3-loop RGB controller. Beautiful appearance shape, aluminum alloy housing with excellent dissipation; tempered glass with good light transmissivity and durable for transportation. flexible bracket and light weight body, easy for installation. IP65 waterproof rank, suitable for outdoor use. Long lifespan over 50,000 hrs. It is the best choice for both outdoor or indoor decoration of architecture.



Application:

Widely used in in/outside commercial buildings , outside lighting decoration, stage, show room, ancient buildings, culture plazas , etc.

Technical parameter:

	0.5M 12X3W RGB 3in1	1,0M 24x3W RGB 3in1
Input voltage	DC24V	DC24V
Max power	50W	100W
Light source	12pcs RGB 3W LED	24pcs RGB 3W LED
LED current	350mA	350mA
Luminous	—	—
Beam angle	50°	50°
Illumination intensity	700lux/2m, 200lux/5m(White color)	1200lux/2m, 300lux/5m(White color)
Control method	RGB controller/DMX512 controller	RGB controller/DMX512 controller
Environment temperature	-20℃~45℃	-20℃~45℃
IP rank	IP65	IP65