

High Power LED landscape Spot Light






SR-A3CM0316
SR-A3CM0318



Waterproof High Voltage Gear & Wiring Box

1. In high voltage mode, the bottom base is allowed to be put high voltage module inside.
2. In low voltage mode, the bottom base is a waterproof connection box.

Graphical Representation for A3CM/SR-A3CB0316 warm white light



Specifications

Housing:	12" Die-casting dark grey powder coated aluminum . T=50-55µm Adhesion of ISO class 1/ASTM class 4B
Glass:	Tempered glass. T=4mm
Lens:	All-in-one optical lens, efficiency≥85%
Cable gland:	IP-68 PG-9 PVC
LED:	Emitter type power LED
PCB:	Excellent heat conductivity aluminum, coefficient of Heat Conductivity≥2.0w/mk
Driver:	Constant current output Single color LED=1-circuit output RGB LED =3-circuit output RGB 3in1 LED =3-circuit output
Operating temperature:	-20℃~ 40℃
Power cable:	H05RN-F 2X1.0mm ² L=2m (low voltage) H05RN-F 4X0.75mm ² L=2m (for RGB)
Spike:	PVC
Mounting base:	Powder coated die-casting aluminum

Item No.	Light Source	Suitable Lens	Lens Beam Angle (°)	Input Voltage (v)	Typical Operating Current (mA)	Typical Consumption (w)	Typical Luminance (lm)
SR-A3CM0318	3×2W RGB 3in1	L0330D050HY	30	12V DC	R=120 G=175 B=178	R=2.9 G=4.2 B=4.3	R=70 G=113 B=31