

Product description

Our Moroccan tiles can be used both as floor and wall tiles. Works great in any indoor environment but also in outdoor spaces, oranges or the like. Gilds any room with its beautiful pattern and unique color combinations. The tiles work well with underfloor heating!!

Each plate is unique as it is made by hand. Made in shape with its specific beautiful pattern for the desired design. Coloring with only organic color pigments where the color goes about 5mm down in the plate. The surface is very durable and can be sanded if necessary.

Our plates are manufactured under fair conditions where we guarantee fair wages, good working conditions and without child labor on site.

Enjoy this wonderful product and let it gild your home with good conscience.

Technical info

Ingredients: Portland cement, silica sand, marble flour, water and organic color pigments.

Manufacturing method: handmade plates in shape, hydraulically pressed, slow burning process!

Dimensions: 200x200x18 mm

Application: bathroom, kitchen, hallway and other indoor environment as well as outdoor space or the like. Also works in an unprotected outdoor environment, provided that proper work is done and that the fixing and jointing material are adapted for outdoor use. Keep in mind that UV radiation can fade the colors over time.

Treatment: Clinker and Stone impregnation that seals the surface and gives a repellent surface. Follow the instructions on packaging. <http://www.mpdij.com/index.php/produkter/kakel-fog/klinker-sten-impregnering/>

Instructions treatment/tiling

Step 1: Tiling

The substrate must be stable, even and well balanced. Make sure the tiles are wet. Let excess water come off.

Add tile adhesives to both the surface and the tile with a coarse toothed putty. It should be planned for a consumption that exceeds normal to offset any differences in the thickness of the plates.

Only use a firm hand when balancing to avoid breaking the tile. Be sure to clean during the tiling process, as the tiles are sensitive before protective treatment.

Step 2:

After tiling treat the tiles with clinker and stone impregnation 2 times. This prevents dirt from entering the plate. Note !! Treatment before grouting to prevent grout residue from penetrating the open pores and causing discoloration. The treatment makes the tile dirt and water repellent but it is still completely diffusion open. (However, it does not prevent discolored joint residue from discolouring.) The original matte raw appearance of the plate is preserved.

Be sure to wipe away any dust and other loose particles with a dry cloth before starting treatment. Follow manufacturer's instructions on the product. Please note that the treatment does NOT prevent grout residues from burning on the surface if you do not wash them immediately !!!

Step 3: Grouting

It is possible to use ordinary grout designed for tiles. Choose the color of the joint that is similar to the bottom color of the plate. Avoid black or white joint as it may discolor. We recommend light joint to light plate and dark to dark plate.

NOTE !! When grouting, be sure to remove excess grout and wash with water immediately. We advice to not work too large areas at a time, but to work gradually and keep clean afterwards.

Attention grouting can be done no earlier than 24 hours after step 1. The grout is recommended to be mixed with a larger portion of water than normal to make it more easily worked and because the tiles absorb more water than ceramic tiles. In bathrooms and on all surfaces with heating loops, at least 3-4mm seam is recommended for heat transfer and movement. Attention !! Underfloor heating must not be switched on until no earlier than 10-12 weeks after the work has been completed.

As soon as the sealant is finished and the excess is removed, the residue should be washed away with water and a coarse sponge. Rinse frequently. The pre-treatment does NOT guarantee that grout residue burns. Important to carefully remove all residue.

After grouting, it may occur a foggy appearance on the tiles. This is easily removed with soap before finishing.

After-treatment:

(There are many different products for treatments on the market so this should only be seen as examples)

Alt1. Soap- Intensive treatment with neutral soap mixed with very little water. This gives a beautiful! shines and makes the floor easier to maintain. Should be repeated after wear and environment. !!

Alt2. Linseed oil wax from Allbäcks, which is an environmentally friendly alternative. Provides a comfortable easy-care surface. Keep in mind that the wax can give a yellowish tone on white tiles. Recommended to try on a tile first. Treatment is repeated after environmental and wear

Alt3. Stone Brite protects and enhances the color. Follow the manufacturer's instructions. Wipe dry with a dry cloth. If you use Stone Brite be careful! by following the instructions on the bottle - no puddles should be formed.

<http://www.mpdij.com/index.php/produkter/kakel-fog/stone-brite/>

Alt 4: OSMO hardwax oil. Follow instructions from manufacturer.

In particularly vulnerable places such as restaurants, entrances and bathrooms, it may be advisable to repeat treatments periodically after wear.

NOTE !! Do not use strong detergents. Care only with soap.

Outdoors

Keep in mind that when tiling outdoors, frost-proof fixing and jointing must be used. Colors are bleached by sunlight but this can be countered with treatment with Klinker and stone impregnation and Stone Brite which both contain a UV protection.

Operation error

The preparatory work and following our advice for tiling is of the utmost importance !! Discoloration due to residual joint residue or due to puddle formation when using too much treatment agent, inadequate cleanliness, careless handling are examples of problems that can arise at the moment of construction! is about handling errors. We do not accept responsibility for inadequate work, handling errors and do not accept any complaints from already placed tiles.

Also note that when using underfloor heating, this should not be turned on until recommended time and should not be used with excessive heat.

Our Moroccan tile is handmade, minor variations in color and pattern may occur. On the other hand it gives the vivid expression and unique character of these fantastically beautiful tiles.

If you have any questions, you are of course always welcome to contact us for advice.