
TECHNICAL DATA SHEET

Rosenberger®

ADAPTOR
BNC 50 Ω PLUG - JACK

51S201-K00N5





All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to	IEC 60169-8, MIL-PRF-39012, CECC 22120

Documents

N/A

Material and plating

Connector parts	**Material**	**Plating**
Center contact plug side	Brass	AuroDur®, gold plated
Center contact jack side	CuBe	AuroDur®, gold plated
Outer contact	Brass	Flash white bronze over silver(e.g. Optargen®)
Body	Brass	Flash white bronze over silver(e.g. Optargen®)
Dielectric	PTFE	
Gasket	NeopreneCR 50C6	

RF_35/12.04/3.0

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel.: +49 8684 18-0
Fax: +49 8684 18-499
email: info@rosenberger.de

TECHNICAL DATA SHEET	Rosenberger®
ADAPTOR BNC 50 Ω PLUG - JACK	**51S201-K00N5**

Electrical data

Impedance	50 Ω
Frequency	DC to 10 GHz
Return loss	≥ 35 dB, DC to 2 GHz ≥ 22 dB, 2 to 3 GHz ≥ 18 dB, 3 to 4 GHz
Insertion loss	$\leq 0.05 \times \sqrt{f\ [GHz]}$ dB, DC to 4 GHz
Insulation resistance	$\geq 5 \times 10^3$ MΩ
Center contact resistance	≤ 1.5 mΩ
Outer contact resistance	≤ 1 mΩ
Test voltage	1500 V rms
Working voltage	400 V rms
Power handling (at 20 °C, sea level, VSWR 1.0)	≤ 80 W @ 2 GHz

Mechanical data

Mating cycles	min. 500
Center contact captivation: axial	≥ 15 N

Environmental data

Temperature range	-55°C to +155°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. B
Shock	MIL-STD-202, Meth. 213, Cond. G
Moisture resistance	MIL-STD-202, Meth. 106
2002/95/EC (RoHS)	compliant

Tooling

N/A

Suitable cables

N/A

Packing

Standard	100 pcs in box
Weight	20.3 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date
Inge Mühlauer	20/07/04	Chr. Entsfellner	13/03/08

Rev.	Engineering change number	Name	Date
e00	07-0154	S. Huber-Siegl	13/03/08

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel.: +49 8684 18-0
Fax: +49 8684 18-499
email: info@rosenberger.de