

AIS74

4 dB AIS Glass Fibre Antenna 1.36 m

Long range high gain International Maritime AIS Antenna for professional use

- Economical replacement for all professional marine AIS antennas
- Improved gain compared to other high quality marine AIS antennas
- Reduced antenna weight compared to similar marine AIS antennas

Electrical Specifications:

Frequency	161.5 - 162.5 MHz (International AIS-band)
Bandwidth	1 MHz
Antenna Type	End-fed full 1/2 λ dipole - no groundplane needed
Impedance	50 Ohm
VSWR	< 1.3:1
Polarisation	Vertical
Gain	4 dB (Marine), 0.5 dBd, 2.6 dBi
Radiation Pattern	Omni-directional
Max. Input Power	150 W
Antistatic Protection	Direct Ground (DC-short)

Mechanical Specifications:

Color	White and chrome
Length	1360 mm
Weight	220 g
Mounting	On 1" threaded pole (G1"-11 thread) with Revolving Nut Kit or on optionally brackets
Mounting place	On rail, mast or deck
Materials	PU-painted glass fibre, copper, PCB, PE and chrome plated solid brass
Survival Wind Speed	55 m/s (125 mph)
Operating temperature	-55C to +70C (IEC 60068-2-1, IEC 60068-2-2)
Connector	UHF-female
Cable	No cable supplied



Datasheet

2 / 4

Ingress Protection	IP66
Vibration	IEC 60068-2-6, IEC 60068-2-64
Serial no.	On product label

Ordering information:


P/N	12074-000 (Antenna only - bulk packing)
P/N	12074-001 (Antenna only - in Polybag)
P/N	12074-002 (Antenna only - in Carton tube)
P/N	12074-431 (Antenna + 1" Revolving Nut Kit - in Polybag)
P/N	12074-432 (Antenna + 1" Revolving Nut Kit - in Carton tube)

Packaging Information:


Type	Bulk packing or individually packing in Polybag or Carton tube (See "ORDERING INFORMATION")
Size	Approx. 1.5 m



Outline Drawing



Typical Radiation Pattern



Typical VSWR

