



Quality is in our nature

Motorcycle oils 4T - Fully Synthetic

# Eurol Sportbike 5W-40 Fullysyn

## Fully synthetic motor oil for 4-stroke motorcycles

### Description

Eurol Sportbike 5W-40 Fullysyn is a fully synthetic engine oil and contains a dedicated ester technology to provide extra protection against wear, deposits, sludge and oxidation under all conditions.

This oil can also be used in motorcycle transmissions where an API SF, SG, SH, SJ or SL oil is prescribed.

Eurol Sportbike 5W-40 Fullysyn is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol Sportbike 5W-40 Fullysyn offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised. Eurol Sportbike 5W-40 Fullysyn has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the

selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

At low temperatures Eurol Sportbike 5W-40 Fullysyn and 5W-50 rapidly provide a solid lubricant film for an optimum protection of the engine at cold starts.

### Specifications

#### Performance level

API SL  
JASO MA  
JASO MA2

### Physical properties

Colour	Brown	
Density at 20°C	0.8517 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	87.9 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.8 cSt	ASTM D 445
Viscosity Index	177	ASTM D 2270
Viscosity, dynamic (CCS)	5750 cP	ASTM D 2602
Flash point	201 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Available in 1L - 20L - 60L - 200L - 210L - IBC - BULK

E100102  
Version 1.0, 03-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com