



Quality is in our nature

Transmission oils - Fully Synthetic

Eurol Fultrax 75W-140 LS

Fully synthetic "limited-slip" gear oil

Description

Eurol Fultrax 75W-140 LS is a fully synthetic gear oil and has especially been developed for heavy duty transmissions demanding a high viscosity oil, resisting high loads, high pressures and shock loads.

Eurol Fultrax 75W-140 LS is recommended for hypoid transmissions, hub reductions and differentials with or without 'limited slip systems' as used in modern cars.

Eurol Fultrax 75W-140 LS can also be used in many other drive line systems where an API GL-5 gear oil, whether or not with 'limited slip' characteristics, by the OEM is prescribed.

Eurol Fultrax 75W-140 LS has a very high viscosity index, very good low temperature fluidity characteristics and will 'stay-in-grade' even under the most severe working conditions.

Eurol Fultrax 75W-140 LS is based on the most modern additive technology, combined with high quality

synthetic base stocks. Therefore, this lubricant offers a better protection against thermal oxidation and reduces corrosion and wear. Seals are not affected by this product. Special friction reducers make this oil suitable for 'limited slip' applications in both passenger cars as well as in commercial vehicles, tractors and earthmoving equipment. The undesirable noise when taking a turn, is being avoided by using this lubricant.

Specifications

Performance level

- API GL-5
- Ford WSS-M2C192-A
- Scania STO 1:0
- BMW 83 23 9 407 870
- BMW 80 23 2 282 583
- GM/Opel GM 12346140

Physical properties

Colour	Yellow	
Density at 20°C	0.881 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	190 cSt	ASTM D 445
Viscosity, kinematic at 100°C	27.5 cSt	ASTM D 445
Flash point	200 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Available in 1L - 20L - 60L - 200L - 210L

E110077
Version 1.0, 03-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com