



Quality is in our nature

Transmission oils - Fully Synthetic

Eurol MTF 75W-85 FE GL5

Full synthetic gear oil with fuel-saving properties

Description

Eurol MTF 75W-85 FE GL5 is a fully synthetic fuel-saving transmission oil, which can be used in manual transmissions and final drives, for which GL-5 is required.

Eurol MTF 75W-85 FE GL5 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Eurol MTF 75W-85 FE GL5 has an excellent high load carrying capacity for an excellent absorption of sudden peak loads. The viscosity decrease due to heavy loads is only slightly, which will extend oil drain intervals (and in some cases lifetime filling) and ensures proper viscosity.

Eurol MTF 75W-85 FE GL5 contains special friction modifiers, which ensure sustainable fuel saving and less heat development. In addition, this oil is ideal for limited slip differentials.

Eurol MTF 75W-85 FE GL5 ensures adequate lubrication at both very low, as very high temperatures and protects

against corrosion, wear, thickening and deposits.

Eurol MTF 75W-85 FE GL5 is compatible with most elastomers and seal materials and does not foam under extreme loads.

Specifications

Performance level

LANCIA

API GL-5

MB 235.7

ZF TE-ML 18

Recommended for use

VW G 055 190 A2

VW G 052 190 A2

VW G 052 145 A1

Fiat

BMW

Alfa Romeo

Physical properties

Colour	Amber	
Density at 20°C	0.87 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	81.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.1 cSt	ASTM D 445
Flash point	190 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

Available in 1L - 20L - 60L

E110081

Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com