DOUBLE SOCKET

HW 050/2



HW 050/2

Double socket
139 mm
Article number: 92305001

Cavity wall double socket, flame resistant, for plate thicknesses from 1 to 40 mm, with moulded patented combi jumpers and punching tool, device screw spacing 60 mm

drilled hole Ø 2 x 68 mm, 50 mm deep, Combination spacing 71 mm

IP30

Technical data

Measures

Height:	139 mm

Material:

Box:	polypropylene, flame-retardent
Cover:	polypropylene, flame-retardent
material:	Polypropylene

Other attributes

Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP30 - acc. EN 60529 / DIN VDE 0470-1

Accessory

ES-10 - Installation screw
ES-18 - Installation screw
ES-25 - Installation screw
HW LFR-68 - HW hole cutter

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 40° C:	50%
Max. rel. humidity at 25° C (short term):	-

Günther Spelsberg GmbH + Co. KG · Im Gewerbepark 1 · D-58579 Schalksmühle · Germany · Phone: +49 (0) 23 55 / 892-0 · Fax: +49 (0) 23 55 / 892-299