

Technical specifications beer tank

Technische specificatie biertank
Technische Spezifikation Biertank

Beer tank horizontal; 3,9 barg.(20°C); PED 2014/68/EU - inliner use Biertank horizontaal; 3,9 bar (20°C); PED 2014/68/EU - inliner gebruik Biertank liegend; 3,9 barü (20°C); PED 2014/68/EU - Inliner geeignet	
<u>Code number</u> Kode nummer Kodenummer	61016708
<u>Content</u> Inhoud Inhalt	1000/1020 Liter
<u>Single walled</u> Enkelwandig Einwandig	Not applicable Niet van toepassing Nicht anwendbar
<u>Double walled</u> Dubbel wandig Doppelwandig	Tank inside completely pickled; outside copper and finished with clear lacquer Tank binnen compleet gebeitst; buitenzijde koper en blank gelakt Tank innen komplett gebeizt; Aussenseite Kupfer und blank lackiert
<u>Cooling</u> Koeling Kühlung	Copper coils suitable for ice water Koperen leidingen geschikt voor koelwater Kupferleitungen, geeignet für Eiswasser
<u>Insulation</u> Isolatie Isolierung	35 mm. cfc polyurethane foam 35 mm. cfk vrij PU schuim 35 mm. PU-Schaum
<u>Material</u> Materiaal Material	1.4301 / outside copper material 1.4301 / buitenzijde koper 1.4301 / Aussenseite Kupfer
<u>Diameter</u> Diameter Durchmesser	Ø 791/860 mm
<u>Length</u> Lengte Länge	+/- 2350 mm
<u>Outlet</u> Uitloop Auslauf	Standard under - Bier drive Uitloop Standaard onder - Bier Drive Auslauf Standard Unten - Bier drive
<u>Material outershell</u> Buitenmantel materiaal Aussenmantel Material	copper koper Kupfer
<u>Connection cooling</u> Aansluiting koeling Anschlüsse Kühlung	Nipple 5/8" male - at the front side Nippel 5/8" buitendraads - aan de voorkant Nippel 5/8" Aussengewinde - an der Vorderseite
<u>Man hole cover</u> Mangatdeksel Mannlochdeckel	310x440 mm removable 310x440 mm uitneembaar 310x440 mm herausnehmbar
<u>Sight glasses</u> Kijkglazen Schaugläser	DN 80
<u>Connection Piercing unit</u> Aansluiting insteek unit Anschluss Ansticharmatur	Bier Drive Piercing unit Bier Drive Insteekunit Bier Drive Ansticharmatur
<u>Connection CO2 armature</u> Aansluiting CO2 armatuur AnschlussCO2 Armatur	Nipple 3/4" male Nippel 3/4" buitendraad Nippel 3/4" Aussengewinde