

AC POWER SUPPLY SPECIFICATION



MODEL NO - RND 320-00072

INPUT

INPUT VOLTAGE	100 to 240 VAC
INPUT FREQUENCY	60/ 50 Hz
PROTECTIVE DEVICE	Fuse, 2A 250V
NO LOAD POWER CONSUMPTION	<0.21W
INPUT FULL LOAD CURRENT (at 100 Vac)	xxx A

OUTPUT

OUTPUT VOLTAGE	24V dc
OUTPUT CURRENT	2500mA

OVERALL PERFORMANCE

TOTAL OUTPUT POWER	60 W Max
EFFICIENCY	Comply with ErP; level VI

PROTECTION

■ OVER CURRENT PROTECTION	■ SHORT CIRCUIT PROTECTION
■ OVER VOLTAGE PROTECTION	■ L.P.S (Limits for power source)
■ OVER POWER PROTECTION	□ AUTOMATIC THERMAL PROTECTION

HI-POT

INPUT TO OUTPUT	3000Vac 5 mA 50 Hz
INPUT TO CASE	3000Vac 5 mA 5Hz
OUTPUT TO CASE	500 Vac 5 mA 50Hz
ISOLATION RESISTANCE	100 M Ohms I/P-O/P I/P/Enclosure
APPLIANCE	Class II

ENVIRONMENTAL

OPERATING TEMPERATURE	0 °C to 40 °C
STORGE TEMPERATURE	-20 °C to 60 °C
OPERATING HUMIDITY	20%-85% RH. NON-CONDENSING
STORGE HUMIDITY	10%-90% RH. NON-CONDENSING

APPROVAL

SAFETY STANDARDS	EN 62368-1:2014+A11:2017
EMC	EN 61204-3:2000

RELIABILITY

MTBF	30000 Hours min
BURN-IN	4 Hours 25°C, full load, 220Vac, 50Hz

MECHANICAL SPECIFICATION\

DIMEMSION	118.0 mm(L)* 51.0 mm(W)* 33.7 mm(H) (excluded plug) 118.0 mm(L)* 51.0 mm(W)* 71.0 mm(H) (included plug)
WEIGHT	255g (excluding packaging)
INPUT PLUG	Direct plug-in; EU type
OUTPUT CABLE	1.8m Black and white wires,
OUTPUT CONNECTOR	Plug E: 5.5x2.1/12

OTHER SPECIFICATIONS

TIME SEQUENCE	Time sequence should be satisfied to power ON/OFF, restart inpower failure AC switch at ON/OFF AC input DC onput 95%V 100%V 95%V $\leq 1.0S$ $\geq 20m S$
DROP TEST	Test condition: 6 face, each face 1 time 70 cm, on the 5mm wooden board. RESULT: Without opening of case and crack, etc. electric characteristic shall be satisfied light crack after test is acceptable.
ENVIRONMENTAL TEST	LOW TEMPERATURE STORAGE TEST Keep on -30°C(Packing) for 168 hours, and check the action after 3 hours in25°C. RESULT: All normal function and meet specification. HIGH TEMPERATURE STORAGE TEST Keep on +70°C(Packing) for 168 hours, and check the action after 3 hours in25°C. RESULT: All normal function and meet specification. HIGH HUMIDITY STORAGE TEST Keep on +45°C, 95%RH (Packing) for 168 hours, and check the action after3hour in 25°C. RESULT: All normal function and meet specification. TEMPERATURE CYCLE TEST Keep on -45°C(Packing) for 1 hour, then keep on +85°C(Packing) for 1 hourRepeat this cycle until 10 cycle, check the action after an hour in 25°C. RESULT: All normal function and meet specification.

Appearance

