

TECHNICAL DATA ECODRY Sollstar



TYPE

Type designation	ECODRY 1300	ECODRY 650	Individual 300-450	Individual 600-900
Dimensions (W*H*D))mm	2110x1300x830	2110x650x830	2230x300-450x550	2230x600-900x550
Weight (kg)	280 kg	123 kg	from min. 8 pieces	from min. 8 pieces
Min. distance to the ceiling	30 mm	30 mm	30 mm	30 mm
Min. distance to wall (rear)	0 mm	0 mm	0 mm	0 mm
Ambient temperature	6 - 30 °C	60-30 °C	6 - 30 °C	6 - 30 °C
Humidity	0-65% REL	0 - 65% REL	0 - 65 % REL	0 - 65 % REL
Operating limit	4 - 35 °C	4 - 35 °C	4 - 35 °C	4 - 35 °C
Operating voltage	230 V AC 50/60 Hz	230 V AC 50/60Hz	230 V AC 50/60 Hz	230 V AC 50/60 Hz
Connected load	1400w	1400w	350w	350w
Ozone	YES	YES	YES	YES
Socket	optional	optional	optional	optional
Noise level	> 70 dBA	> 70 dBA	> 70 dBA	> 70 dBA
Max. Users	10	5	2	2
Ral (colour)	7038 /7035	7038/7035	7035/7035	7038/7035
Capacity persons	8 sets	4 sets	1 set	2 sets

TECHNICAL DATA ECODRY Sollstar



TYPE				
Type designation	Cabinet 10TS Glove	Cabinet 5/10 TS Boot	Cabinet mask 14TS	Cabinet helmet 8TS
Dimensions (W*H*D) mm	2110x300x500	2110x300/600x500	2110x600x500	2110x600x500
Weight (kg)	51 kg	50kg / 83 kg	83 kg	83 kg
Min. distance to the ceiling	30 mm	30 mm	30 mm	30 mm
Min. distance to wall (rear)	0 mm	0 mm	0 mm	0 mm
Ambient temperature	15 - 25 °C	15 - 25 °C	15 - 25 °C	15 - 25 °C
Humidity	0-65% REL	0 - 65% REL	0 - 65 % REL	0 - 65 % REL
Operating limit	13 - 27 °C	13 - 27 °C	13 - 27 °C	13 - 27 °C
Operating voltage	230 V AC 50/60 Hz	230 V AC 50/60Hz	230 V AC 50/60 Hz	230 V AC 50/60 Hz
Connected load	0.85 kw	0.35 / 0,7 kw	0.7 kw	0.7 kw
Ozone	YES	YES	YES	YES
Socket	NO	NO	NO	NO
Noise level	> 70 dBA	> 70 dBA	> 70 dBA	> 70 dBA
Max. Users				
Ral (colour)	7038 /7035	7038/7035	7038/7035	7038/7035
Capacity persons	10 pairs	5 / 10 pairs	14 pieces of mask	8 pieces of helmet

TECHNICAL DATA ECODRY Sollstar



TYPE			
Type designation	Wall dryer Boot 5/10	Wall dryer Glove 10	Wall dryer Boot 15/20
Dimensions (W*H*D) mm	1984x260/524x385	1984x260x325	2070x860/1148x385
Weight (kg)	29kg / 53 kg	31 kg	106 kg / 131 kg
Min. distance to the ceiling	30 mm	30 mm	30 mm
Min. distance to wall (rear)	0 mm	0 mm	0 mm
Ambient temperature	15 - 25 °C	15 - 25 °C	15 - 25 °C
Humidity	0-65% REL	0 - 65% REL	0 - 65 % REL
Operating limit	13 - 27 °C	13 - 27 °C	13 - 27 °C
Operating voltage	230 V AC 50/60 Hz	230 V AC 50/60Hz	230 V AC 50/60 Hz
Connected load	0.85 kw / 1.7 kw	0.85 kw	1.7 kw
Ozone	YES	YES	YES
Socket	NO	NO	NO
Noise level	> 70 dBA	> 70 dBA	> 70 dBA
Boot/gloves nozzle	320 - 450 mm	260 mm	320 - 450 mm
Ral (colour)	7038 / 7035	7038/7035	7038/7035
Capacity persons	5/10 pairs of boots	10 pairs of gloves	15/20 pairs of boots