

COLD WATER – FOUR WHEELS

The **medium quadro-Series**

Integrated Hose drum

Practical design and features a longer length high-pressure hose complete with folding crank

Total-stop system with delayed motor cut-off

Auto-shutdown feature improves seal lifespan and reduces power consumption

Pressure regulation

Fully adjustable control allows operating pressures to be set to suit any task

Cleaning Agent Intake

Injector system for dispensing of cleaning agents

Integrated water tank

Prevents damage to the high-pressure pump caused by a lack of water

Roto-Mold-Chassis

Virtually indestructible

Figures: quadro 799 TST





		quadro 599 TST		quadro 799 TST		quadro 899 TST	
Technical specifications							
Operating pressure adjustable	bar / MPa	30-150 / 3-15		30-180 / 3-18		30-150 / 3-15	
Max. admissible overpressure	bar / MPa	165 / 16.5		200 / 20		170 / 17	
Connected load	V / ~ / Hz / A	230 / 1 / 50 / 14		400 / 3 / 50 / 8.5		400 / 3 / 50 / 8.5	
Motor speed	Rpm	1400		1400		1400	
Water output	l/min l/h	10	600	13	780	15	900
Power intake / Power output	kW kW	3.3	2.4	5.5	4.0	5.5	4.0
Volume water tank	l	10		10		10	
Power supply cable	m	5		7.5		7.5	
Dimensions L x W x H	mm	780 / 395 / 870		780 / 395 / 870		780 / 395 / 870	
Weight	kg	62		62		62	
Cleaning Agent Intake		●		●		●	
Equipment							
Hose drum		●		●		●	
Steel braided high-pressure hose	m	20		20		15	
Trigger gun with safety catch	Model	M2000		M2000		M2000	
Dirtkiller lance	Nozzle size	● 035		● 045		● 06	
Stainless steel lance with flat jet nozzle	Nozzle size	● M20035		● M20045		● D2506	
Ord.no.		40431		40432		40434	

Fig. Non-marking version (NoM). Info on page 58



For detailed technical information, see page 78-79