




CALDAIA ELETTRICA ISTANTANEA DA 24
A 48 KW A FLUSSO CONTINUO IN ALTA
PRESSIONE

ELECTRIC BOILER FROM 24 TO 48 KW WITH
CONTINUOUS FLOW IN HIGH PRESSURE



SPLIT-E

GENERATORE ELETTRICO D'ACQUA CALDA INDUSTRIALE A FLUSSO CONTINUO IN ALTA PRESSIONE
INDUSTRIAL ELECTRIC HOT WATER GENERATOR WITH CONTINUOUS FLOW IN HIGH PRESSURE

SPLIT-E - GENERATORE ELETTRICO D'ACQUA CALDA INDUSTRIALE A FLUSSO CONTINUO IN ALTA PRESSIONE

INDUSTRIAL ELECTRIC HOT WATER GENERATOR WITH CONTINUOUS FLOW IN HIGH PRESSURE

- Completamente in acciaio inox 304
- Flussostato su ingresso per controllo accensione resistori, montato in verticale per dare possibilità, in caso di guasto della molla, di toglierla.
- Valvola di sicurezza
- Termostato 0-90°C regolabile
- Termostato 70°C fisso a riarmo automatico per doppia sicurezza su ingresso acqua nel primo resistore (se il flussostato si rompe e i resistori scaldano in assenza di acqua, interviene subito)
- QE con comandi utente in bassa tensione 24V
- Sezionatore principale di alimentazione
- Pulsanti ON-OFF per avvio e arresto modalità riscaldamento
- Selettore metà potenza 50%-100% per i modelli a 6 resistori (tutti tranne il 24kW)
- Ritardo di 5 secondi tra passaggio acqua e accensione resistori (per evitare che microperdite o utilizzi sbagliati della lancia, compromettano i teleruttori con troppe commutazioni orarie)
- Resistori coibentati
- Completely in 304 stainless steel
- Flow switch on the input to control the ignition of the resistors, mounted vertically to allow the spring to be removed in the event of a spring failure.
- Safety valve
- Adjustable 0-90°C thermostat
- Fixed 70°C thermostat with automatic reset for double safety on the water inlet in the first resistor (if the flow switch breaks and the resistors heat up in the absence of water, it intervenes immediately)
- QE with low voltage 24V user controls
- Main power switch
- ON-OFF buttons to start and stop heating mode
- Half power selector 50%-100% for the 6-resistor models (all except the 24kW)
- 5-second delay between the water passage and the ignition of the resistors (to prevent micro-leaks or incorrect use of the lance from compromising the contactors with too many time switchings)
- Insulated resistors

ACCESSORI A RICHIESTA / ACCESSORIES ON DEMAND

KIT STAFFA MURO WALL BRACKET KIT	COMANDO REMOTO REMOTE CONTROL
	
Mod. Tutti - All Cod. B.CRDS00814	Mod. Tutti - All Cod. 01AC060

PESI E DIMENSIONI MACCHINA WEIGHTS AND DIMENSIONS MACHINE					IMBALLO PACKAGING			
MOD	A	B	C	Netto/Net	X	Y	H	Lordo/Gross
	[mm]	[mm]	[mm]	[kg]	[mm]	[mm]	[mm]	[kg]
SPLITE 24	690	470	360	32,5	780	540	610	42
SPLITE 36	690	470	360	39	780	540	610	49
SPLITE 42	690	470	360	39	780	540	610	49
SPLITE 48	690	470	360	39	780	540	610	49

		SPLIT-E 24	SPLIT-E 36	SPLIT-E 42	SPLIT-E 48
codice - code		● 01SL600	● 01SL700	● 01SL800	● 01SL900
pressione - pressure	[bar]	3/250	3/250	3/250	3/250
portata - flow rate	[lt/h]	300/600	420/720	480/840	600/900
salto termico - temperature raising (portata/flow rate)	[°C - l/min]	41 - 8	48 - 10	47 - 12	50 - 13
corrente assorbita - absorbed power	[A]	33	49	57	65
potenza assorbita max - max. absorbed power	[Kw]	24	36	42	48
alimentazione - supply voltage	[V - ph - Hz]	400-3-50/60	400-3-50/60	400-3-50/60	400-3-50/60
massima temp. - max. temp.	[°C]	90	90	90	90