

3006102036

## **EHS-2200**

Rotary Light 220VAC



### **DESCRIPTION**

- Used in noisy areas to indicate a call
- Can be used for all Vingtor-Stentofon systems
- Used together with relay unit

Rotating beacon in painted mild steel housing, for less aggressive environments. Enduring with low noise friction-gear.

## SPECIFICATIONS

| GENERAL           |                                      |
|-------------------|--------------------------------------|
| Operating voltage | 230VAC (50 - 60Hz) +- 10%            |
| Lamp source       | 40 W Ba-15d                          |
| Rated current     | 200mA                                |
| Flash frequency   | 180 r.p.m                            |
| Operating temp    | -10°C to +50°C                       |
| Material          | Housing: Painted mild st. / Lens: PC |
| Housing Colour    | Grey                                 |
| Duty cycle        | 100%                                 |
| Connection        | 1mtr. cable                          |
| IP-class          | IP-54                                |
| Dimensions (mm)   | 148Ø x 215H                          |
| Weight            | 1.1 kg                               |
| Storage temp      | -10°C to +55°C                       |
| Relative humidity | <95% Non-condensing                  |
| ORDER NUMBER      | DESCRIPTION                          |
| 3006102033        | EHS-220B Rotary Light 220VAC Blue    |
| 3006102034        | EHS-220G Rotary Light 220VAC Green   |
| 3006102035        | EHS-220K Rotary Light 220VAC Clear   |
| 3006102037        | EHS-220R Rotary Light 220VAC Red     |