

3006202045

IRR-24

Relay Box



DESCRIPTION

- Built-in timer circuit. 20 sec. signalling time as standard
- Alarm stop button
- Delivered for bulkhead mounting
- Suitable for installation in noisy areas
- For use in Pro700 and VSP systems

IRR-24 is a separate relay timer unit for operation of 24V DC visible and / or audible signal units.

SPECIFICATIONS

GENERAL

Dimensions (WxHxD)	110 x 80 x 63 mm
Mounting	4 x 4 mm screws
Weight	0.35 kg
Housing	Polyester
Colour	Grey
IP-rating	IP-66
Cable entry	3 x PG-11
Connections	Screw terminals
Operation voltage	24V DC

Created: 25.07.2014, updated: 08.05.2020

page 1/2

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Vingtör-Stentofon products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend. Zenitel – All rights reserved.

TECHNICAL DIMENSIONS

