



JK TAILGATE TABLE

INSTALLATION INSTRUCTIONS

JK 07-10 P/N JK008

JK 11-18 P/N JK009

MADE IN SWEDEN

Notes on the Installation

Estimated installation time: 2 hours

Due to manufacturing variations, some Jeep model years might have slight differences. Before drilling any holes, make sure to verify the fitment of the tailgate table with the tailgate both open and closed.

General Installation Information

Off-roading is a hands-on hobby, and this product is designed for user installation. However, if you feel unsure please remember that safety is crucial when working with motor vehicles, whether on-road or off-road.

We cannot take responsible for any damage caused by incorrect installation so please don't hesitate to reach out if you have any questions. We're available to provide support and you will find contact information on our webpage.

If the installation feels too challenging, we also offer an **installation service**. More information is available on our website.

Installation Tip

While the table can be installed by one person, having an extra set of hands makes the process much easier. Take your time and proceed carefully—the reward will be a cleaner and more professional looking installation.

What's in the Box

Your **tailgate table** comes mostly **assembled**. However, you'll need to:

- Install the **sliding table stops**
- Depending on your Jeep model, install the ***folding table side locks***

Care and Use

Keeping your table clean will ensure it looks great for years. Wipe off grease, food residue, or grime after each use.

Maintaining the Slide-Out Oak Board

- The oak board is hard wax oiled for protection. Reapply oil occasionally for maintenance. We use Osmo brand satin oil, but any similar product will work.
- If the surface gets scratched (e.g., from knives or tools), a light sanding before reapplying oil will help restore the finish.

Adjusting the Hinge Bolts

- The hinge bolts control how easily the table unfolds. Over time, the plastic washers that protect the paint may loosen. Simply tighten the bolts slightly to maintain a rattle-free drive.

Installation Instructions

Step 1: Prepare the Table for Installation

- Slide out and remove the wood board to make handling easier.

Step 2: Positioning the Table on the Tailgate

1. Align the table vertically by using the included spacers to ensure correct height. (Pic 1)



2. Make sure to void drilling into spot welds when positioning horizontally:

- **Pre-facelift models:** Position the table a few millimeters from the **first right-hand fold** in the sheet metal (Pic 2).
- **Post-facelift models:** Position the right side of the table close to the **second fold** (Pic 3).



3. Check fitment with the tailgate closed and opened.

- For **pre-face lift JK models with a subwoofer**, pay attention so that the table doesn't interfere with the subwoofer when the trunk is closed.
- For **post-face lift models or pre-facelift without subwoofer**, pay attention to the lower right corner facing toward the front of the Jeep.

Step 3: Mark and Drill the Mounting Holes

1. Hold the table in position and **mark the four outermost holes** with a felt pen (Pic 4). Again making sure not to mark a spotweld.
 - This can be done alone, but an extra pair of hands helps.
 - Alternatively, install one **nutsert**, mount the table, mark the next hole, and repeat.



2. Set the table aside, then **center punch** the marked spots to ensure accurate drilling.
3. **Drill a small pilot hole**, then enlarge it to 9.5-10mm using a step drill.
4. Touch up the exposed metal with paint before installing the nutserts to prevent rust.

Step 4: Install the Nutserts

1. Use the **provided nutsert tool** if you don't have access to a dedicated tool (Pic 5, 6 & 7). It can be used with a wrench/spanner or an impact driver.



2. If using the provided tool, install the **nutsert on the bolt** as far as it goes, ensuring the **order of nuts and shims** is correct.
3. A small **dab of Loctite** can be applied near the nutsert head for extra fastening and rust protection.
4. Insert the nutsert into the drilled hole.
5. Use a **spanner wrench** on the drilled out nut to hold it in place while tightening with the bolt (Pic 8).
 - **Three revolutions** is typically enough.
 - To keep track of the revolutions, mark the socket before starting.



Step 5: Attach the Tailgate Table

1. Place the **distance spacers** between the table and the tailgate.
 - The **countersunk end** of the spacers should slip over the nutserts.
2. A 12mm **spanner wrench** fits around the distance spacer helps with alignment (Pic 9).



3. Do not **overtighten the nutserts**—they are strong but only needs 10 Nm.
 - If you don't have a torque wrench, **snug is tight enough**.

Step 6: Install the Oak Board and Finishing Touches

1. Slide the **oak board** back into the table.
2. Install the **round slide stops** by pressing them into place (Pic 10).



3. If the **folding table side locks** aren't installed yet, do so now (Pics 11 & 12).

- Note that the locks can be **set in the open position** by slightly turning the knob.



4. Adjust the **rubber bump stop** to apply pressure to the oak board when closed—this prevents rattling (Pic 13).



Step 7: You're All Set!

Now it's time to hit the trails—cook up a meal, enjoy a drink, and find your way further into the woods!

/Falken Fabrication

