



2 STAGE OIL-SEALED ROTARY VANE VACUUM PUMPS

Atlas Copco

GVD 3-5



FEATURES AND BENEFITS

- 48 dB(A) and intrusive frequencies minimized.
- Dual mode. Suitable for high throughput and high vacuum applications.
- Easy-to-use gas ballast.
- Fast acting inlet valve for system protection.
- High torque, dual voltage/dual frequency motor, electronic start relay.
- Efficient high pressure lubrication.
- Oil-tight with printed gaskets, effective shaft seals.
- Clamped-in sight glass.
- Oil box well contains filling spills.
- Hi-tech polymer blades, large diameter, easy-clean oil passages.
- Consistent, built-in quality, cast bar construction.

TECHNICAL SPECIFICATIONS GVD 3-5

	GVD 3		GVD 5	
	50 Hz	60 Hz	50 Hz	60 Hz
Displacement	3.7 m ³ h ⁻¹ / 2.2 cfm	4.5 m ³ h ⁻¹ / 2.6 cfm	5.8 m ³ h ⁻¹ / 3.4 cfm	7.0 m ³ h ⁻¹ / 4.1 cfm
Speed (Pneurop 6602)	3.3 m ³ h ⁻¹ / 2 cfm	3.9 m ³ h ⁻¹ / 2.3 cfm	5.1 m ³ h ⁻¹ / 3.0 cfm	6.2 m ³ h ⁻¹ / 3.7 cfm
Ultimate vacuum (total pressure) without gas ballast	2.0 x 10 ⁻³ mbar / 1.5 x 10 ⁻³ Torr		2.0 x 10 ⁻³ mbar / 1.5 x 10 ⁻³ Torr	
Ultimate vacuum (total pressure) with gas ballast in position 2	1.2 x 10 ⁻¹ mbar / 9.1 x 10 ⁻² Torr		1.0 x 10 ⁻¹ mbar / 7.5 x 10 ⁻² Torr	
Inlet connection	DN25 ISO-KF		DN25 ISO-KF	
Outlet connection	DN25 ISO-KF		DN25 ISO-KF	
Max. outlet pressure	0.2 bar / 3 psig gauge		0.2 bar / 3 psig gauge	
Max. inlet pressure for water vapor	80 mbar / 60 Torr		50 mbar / 38 Torr	
Max. water vapor pumping rate	60 gh ⁻¹		60 gh ⁻¹	
Weight (without oil)	25 kg / 55 lb		25 kg / 55 lb	
Motor power	450 W	550 W	450 W	550 W
Power connector 1-ph*	IEC EN60320 C13		IEC EN60320 C13	
Maximum oil capacity	0.7 litre		0.7 litre	
Minimum oil capacity	0.42 litre		0.42 litre	
Noise level	48 dB(A) @ 50 Hz		48 dB(A) @ 50 Hz	

* 2m long 1-phase cable to be ordered separately. 3-phase motors connect directly to terminal box.

APPLICATIONS