

MAX505

Max Cases are our watertight line, created to offer superior protection from the elements, water, dust and impacts when transporting fragile and valuable objects.

IP67 certified, NATO coded and enabled to **STANAG 4280** and **DEF STAN 81-41** these cases are suitable for a wide range of applications such as photography, scuba diving, outdoor sports, military, special corps, broadcasting, the manufacturing industry in general and all those sectors where is required an exceptional resistance to impacts and atmospheric agents.

FEATURES

- Waterproof and dustproof
- Watertight seal around lid
- Automatic pressure release valve
- Easy to open double throw latches
- Load tested soft grip handle
- Holes for double padlocking
- Holes for shoulder strap
- Stackable interlocking system
- Thick body material
- Extra fixing points
- Fully length hinges
- Nylon pins, corrosion free
- Cubed foams in the bottom and convoluted foams in the lid available as standard
- Screen printing space and rectangular resin label space on the lid
- Body and handle: polypropylene copolymer
- Latches: nylon
- Pins: nylon + 30% fiberglass
- O-ring: polymer



COLOURS



TECHNICAL SPECIFICATIONS

- EXTERNAL DIMENSIONS: 555 x 428 x H211 mm (21.85 x 16.85 x H8.31 inch)
- INTERNAL DIMENSIONS: 500 x 350 x H194 mm (19.69 x 13.78 x H7.64 inch)
- LID-BOTTOM DEPTH: 58 + 136 mm (2.28 + 5.36 inch)
- WEIGHT W/O FOAM: 3.90 kg - 8.60 lbs.
- WEIGHT WITH FOAM: 4.38 kg - 9.66 lbs.
- INTERNAL CUBIC VOLUME: 33950000 cubic millimeters - 1.199 cubic feet
- VOLUME CAPACITY: 33.95 Lt
- HANDLE CAPACITY: 30 kg
- PCS PER CARTON: 1
- WEIGHT OF THE FULL CARTON W/O FOAMS: 4.74kg - 10.45 lbs.
- WEIGHT OF THE FULL CARTON WITH FOAMS: 5.22kg - 11.51 lbs.
- MOLDING: injection molding
- RANGE TEMPERATURE: -30 / 90°C (-22 / 194°F)
- COSTUMIZATION: personalized nameplate/resin label
- ACCESSORIES: cubed foams, lid organizer, padded dividers, padded shoulder strap