

DECOSTAR 35 TITAN

46890 SP




Product benefits

- Brilliant accent light
- Constant bluish appearance of the light escaping at the back of the reflector
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Constant luminous intensity and constant color location throughout
- Flat clear shield
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter

Product features

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index Ra: 100
- Color temperature: 2,800 K
- Base: BA15d, GY4



Technical data

Electrical data

Rated wattage	20 W
Nominal wattage	20 W
Nominal voltage	12 V
Rated number of switching cycles	1000000 ¹⁾
Rated power factor λ	1.00

¹⁾ At 1 s on / 1 s off

Light technical data

Luminous intensity	3500 cd
Beam angle	10 °
Rated color temperature	3000 K
Rated color rendering index Ra	100
Rated starting time	0.0 s
Rated warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.80

Dimensions & weight

Overall length	42.0 mm
Diameter	35.0 mm
Outer bulb	MR35

Colors & materials

Rated lamp mercury content	0.0 mg
Mercury-free	Yes

Lifespan

Nominal lamp life time	4000 h
------------------------	--------

Lifespan

Rated lamp life time	4000 h
----------------------	--------

Additional product data

Base (standard designation)	GU4
Design / version	Reflector

Capabilities

Dimmable	Yes
Burning position	hs30

Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4050300529301	Folding carton box 1	38mm x 34mm x 50mm	19.00g	0.06dm ³
4050300529318	Shipping carton box 10	81mm x 58mm x 178mm	220.00g	0.84dm ³

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.