

Mounting frames



Alixo Standard Frames

Alixo Standard Frames are ideal for mounting HVAC and (refrigeration) technical units on flat or slightly sloped roofs. They are equipped with individually adjustable and removable feet and are suitable for condenser units, VRF/VRV systems, etc. Frames with taller feet (700–900 mm) are supplied with an additional reinforcement kit.

- ▶ material: warm galvanised steel (frame) & recycled HDPE (foot)
- ▶ foot dimensions: 305 x 305 mm;
- ▶ includes integrated anti-vibration mat
- ▶ packaged per box (ALX-8210 & ALX-8219)
- ▶ robust and easy to install and adjust
- ▶ quick and economical; suitable for all roof types
- ▶ no penetration of the waterproof roof membrane
- ▶ optional: sloped anti-vibration mats
- ▶ custom solutions: contact us for more information

art. no.	info	dim. (LxW)	adjustable height	feet	load capacity*
Alixo Standard Frames (boxed)					
ALX-8210-000	Alixo mounting frame	1000 x 1200	250-450	4	175 kg
ALX-8219-000	Alixo extension frame	1000 x 1200	250-450	2	175 kg
Alixo Standard Frames					
ALF-1213-000	Alixo mounting frame	1000 x 1200	700-900	4	175 kg
ALF-1511-000	Alixo mounting frame	1000 x 1500	300-400	4	175 kg
ALF-1513-000	Alixo mounting frame	1000 x 1500	700-900	4	175 kg

*: static load per adjustable foot (indicative)

Accessories Alixo Standard Frames

art. no.	info
cross bars and frame fixing kit	
ALF-1200-000	cross bar 1200 mm
ALF-1500-000	cross bar 1500 mm
ALF-9900-000	Alixo frame fixing kit
anti-vibration mats for 305 x 305 mm feet	
LAV-7312-000	sloped (2.5°) anti-vibration mat
LAV-7315-000	sloped (5°) anti-vibration mat

