

REFRIGERATED UPRIGHT CABINET | ABS



GENERAL FEATURES

GN2/1 Refrigerated upright (600 Lt.)	•
S/S external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (60mm per side)	•
Digital Thermostat	•
Removable Gasket	•
Reversible door	•
Handle along door profile	•
Doors lock fitted as standard	•
Adjustable shelves: 4 Pcs	•
N.2 Adjustable feet + N.2 Rollers at the back	•

TECHNICAL SPECIFICATION

INNER DEPTH	585 mm
INNER HEIGHT	1660 mm
INNER WIDTH	660 mm
DEPTH	720 mm
HEIGHT	1895 mm
WIDTH	780 mm
KW/24H	2.27 Kw
CAPACITY	600 L
NOISE LEVEL	48 dB(A)
CONSUMPTION	200 W
NET WEIGHT	85 Kg
TEMPERATURE RANGE	+2°C ~ +10°C

CERTIFICATIONS



QRX 600

38°C

CLIMATIC CLASS

60 mm

GAS
R600a

NO IMAGE

DETAILS



1. Cabinet suitable for GN2/1 pans
2. Cabinet suitable for N.2 GN1/1 pans
3. Digital Thermostat
4. Lock fitted as standard

SIZES

