

REFRIGERATED UPRIGHT CABINET | ABS



GENERAL FEATURES

600 Lt. Refrigerated upright (GLASS DOOR)	•
White external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (50mm per side)	•
Digital Thermostat	•
Removable Gasket and reversible door	•
Inner LED light	•
Stainless steel external handle	•
Lock and main switch fitted as standard	•
Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf	•
N.2 Adjustable feet + N.2 Rollers at the back	•

TECHNICAL SPECIFICATION

INNER DEPTH	582 mm
INNER HEIGHT	1653 mm
INNER WIDTH	670 mm
DEPTH	769 mm
HEIGHT	1900 mm
WIDTH	775 mm
KW/24H	0 Kw
CAPACITY	600 L
NOISE LEVEL	68 dB(A)
CONSUMPTION	260 W
NET WEIGHT	114 Kg
TEMPERATURE RANGE	+2°C ~ +8°C

CERTIFICATIONS



RCG 600

DETAILS



1. Cabinet suitable for GN2/1 pans
2. Cabinet suitable for N.2 GN1/1 pans
3. N.12 Basket (Dim: 440x290x200 mm)
4. Main switch, digital thermostat and door lock fitted as standard
5. Digital Thermostat
6. External cylindric handle in stainless steel (Steel color for X Version)

SIZES

