

Document shredders DAHLE 616



- High-volume department document shredder
- Door open wide for easy emptying of waste container
- Intuitive, user-friendly illuminated control panel with audio signals
- Device shuts down automatically after 30 minutes without use
- Electronic start and stop function controlled by integrated light barrier
- Automatic paper reverse function clears excess paper
- Convenient feeding and reversing function for manual control
- Automatic safety shut-off when the waste container is full or the door is open
- Optical waste level indicator
- High-quality solid steel cutting rollers made of special steel for guaranteed long lifetime
- All models with security levels P- 6 and P-7 feature integrated oil tank for regular automatic oiling of cutting rollers
- Pull-out waste container
- Powerful motor ensures high performance and longer run times
- Extremely quiet operation
- Convenient swivel castors, two of which are lockable, with 5 cm ground clearance for greater mobility
- Easy-to-reach main switch on rear of device
- Practical cold-device plug can be detached from document shredder
- 5-year guarantee on cutting rollers for models with security levels P-6 and P-7

| | |
|--------------------------------|----------------------|
| Article number | 40630-05177 |
| Entry width in mm | 400 |
| Sheet capacity (80g/sqm)* | 11 sheets |
| Particle size (in mm) | 0,8 x 12 mm |
| Security levels | P-6/F-3/T-6 |
| Autom. oiler | ✓ |
| Oil incl. in ml | 400 |
| running time | Continuous operation |
| CDs/DVDs | - |
| Cards | ✓ |
| Paper clips | - |
| Waste collection volume (in l) | 160 |
| Noise level when idle (db(A)) | 50 |
| Power consumption (W) | 1650 |
| Dimensions H x W x D (mm) | 960 x 734 x 511 |
| EAN | 4007885248929 |



* Maximum number of DIN A4 sheets that can be shredded in a single load under the following conditions: new cutting rollers (oiled if necessary), cold motor, power supply with rated voltage and rated frequency (230V/50Hz; 120V/60Hz). Sheet capacity may be lower and operating noise higher under different conditions. Sheet capacity may also vary due to sheet characteristics and paper feed.