



## OWNER MANUAL

# BR-652VW

### Features:

- \*Car specific 2-way component speaker system
- \*6.5" woofer with paper-fibre cone and rubber surround
- \*Car specific high pass filter included
- \*25 mm / 1" silk dome tweeter
- \*Klippel® optimized
- \*Suitable for VW\*

\*VW is a registered trademark of Volkswagenwerk GmbH



BR-652VW	2-way Component System	
Impedance	4 Ohm	
Frequency response	70-30kHz	
Efficiency 1W/1M	90dB	
Power Handling(RMS)	60W	
Power Handling(max)	120W	
Crossover Frequency	3500 Hz(6/oct)	
Linear Parameters(TSP)	BR-652VW-MID	BR-652VW-TW
Membrane Material	Paper	Silk
Voice Coil Diameter	1"	1"
Resistance(Re)	3.6 Ohm	3.6 Ohm
Resonance Frequency(Fs)	70 Hz	1750 Hz
Mechanical Q factor(Qms)	4.97	
Electrical Q factor(Qes)	0.63	
Total Q factor(Qts)	0.56	
Equivalent air volume Vas	8.2L	
Mechanical mass(Mms)	11.3 g	





# OWNER MANUAL

## BR-652VW

### Physical Dimensions:

