


Technical Data/Specification

Model	RJ-W102S4	RJ-W122S4	RJ-W152S4
Voice Coil Diameter(mm/inch)	83/3.3	83/3.3	83/3.3
Impedance Ohm	Dual 2	Dual 2	Dual 2
Re Ohm	4	4	4
FS Hz	49.31	37.08	32.74
Sd	346.36	514	804
Md g	280	287	250
BL	20.84	23.35	23.07
Qms	4.03	4.496	5.598
Qes	0.79	0.815	0.88
Qts	0.66	0.69	0.76
No	0.092	0.088	0.14
SPL dB	81.7	81.5	83.6
Vas L	6.35	14.53	37.7
Cms	37.27	38.63	41.08
Krm	37.91	30.518	33.18
Erm	0.68	0.7	0.69
MMS g	279.38	476.66	575
MMd	271.97	463.2	548
Kxm	112	107.49	114.52
Exm	0.6	0.706	0.59
Xmax mm	21	21	21
Rms Power(Watts)	3000	3500	3500
Max Power(Watts)	6000	7000	7000



Model:	A	B	C	D
RJ-W102S4	260mm	205mm	220mm	235mm
RJ-W122S4	330mm	230mm	220mm	288mm
RJ-W152S4	395mm	270mm	220mm	350mm