





RJ-W804S3
RJ-W104S3
RJ-W124S3
RJ-W154S3



Technical Data/Specification

Model	RJ-W804S3	RJ-W104S3	RJ-W124S3	RJ-W154S3
Voice Coil Diameter(mm/inch)	65.7/2.58	76.5/3	76.5/3	76.5/3
Impedance Ohm	Dual 4	Dual 4	Dual 4	Dual 4
Re Ohm	6.4	6	6	6
FS Hz	54.72	37.4	37.23	32.8
Sd	188.69	330	502	769
Md g	100	200	200	200
BL	20.72	26.56	27.5	26.779
Qms	3.87	5.3	5.3	5.1
Qes	0.69	0.45	0.507	0.52
Qts	0.58	0.42	0.463	0.47
No	0.073	0.13	0.236	0.42
SPL dB	80.6	83.3	86.3	88.3
Vas L	3.175	12.21	23.96	65.10
Cms	62.8	78.97	66.77	77.44
Krm	28.29	37.67	36.63	34.49
Erm	0.72	0.72	0.18	0.719
MMS g	134.6	229.3	243	302
MMd	131.6	225.8	235.1	290.7
Kxm	111.03	90.77	81.84	91.3
Exm	0.622	0.67	0.68	0.06
Xmax mm	14	17.5	17.5	17.5
Rms Power(Watts)	1200	2500	3000	3000
Max Power(Watts)	2400	5000	6000	6000



Model:	A	B	C	D
RJ-W804S3	218mm	161mm	176mm	182mm
RJ-W104S3	265mm	188mm	226mm	239mm
RJ-W124S3	326mm	213mm	226mm	290mm
RJ-W154S3	396mm	239mm	226mm	358mm

