



GARDEN 2T Hi-Tech

2 Stroke Engine Lubricant for Motorised Garden Tools

Technosynthese

TYPE OF USE

**Specially formulated for 2 Stroke engine garden tools.
Suitable with leaded or unleaded gasoline.**

Motor cultivator, chain saw, lawn mower, ground clearing machine...

MOTUL GARDEN 2T Hi-Tech exceeds specifications of ISO-L-EGD, JASO FC and API TC standards, and is consequently recommended for engines working under very severe conditions or at high revs.

PERFORMANCE

STANDARDS : ISO-L-EGD , JASO FD , API TC

Contains synthetic products with very high combustion properties to reduce smoke and deposits.
Pre-diluted lubricant which mixes instantaneously with gasoline and remains stable.
Reinforced anti-rust and anti-corrosion properties.
Reduces deposits in exhaust pipes and on pistons.
Prevents spark plug from fouling.

RECOMMENDATIONS

Premix ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

PROPERTIES

Colour the gasoline in red.

Density at 20°C (68°F)	ASTM D1298	0.864
Viscosity at 40°C (104°F)	ASTM D445	66.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	9.9 mm ² /s
Viscosity index	ASTM D2270	130
Flash point	ASTM D92	117°C / 243°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.
Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web site : www.motul.com

09/10