



DS SUPER AGRI 15W-40

**Multipurpose Lubricant
For Farm machines**

TYPE OF USE

Multipurpose Lubricant for Modern Farming Machines : Diesel engines turbocharged or not, gasoline engines / Transmissions / Wet Brakes / Hydraulic systems.

Recommended for the following farm machines working in normal conditions : JOHN DEERE, MASSEY FERGUSON, CASE, INTERNATIONAL HARVESTER, RENAULT, DEUTZ NEW HOLLAND / FORD / FIAT AGRI...

PERFORMANCE

ENGINE STANDARDS SPECIFICATIONS	SAE 15W40. API CF-4 / SF – API CH-4 / ACEA E5 (soot control). MB page 227.1
TRANSMISSIONS STANDARDS SPECIFICATIONS / PERFORMANCE LEVELS	SAE 80W90. API GL-4. GM ALLISON C4 - CATERPILLAR TO 2.- ZF TE.ML.06B/06C/07B NEW HOLLAND / FORD M2C 159 B – FORD 30/40 JOHN DEERE JDM 27 - MASSEY FERGUSON MF 1139 - MF 1144
HYDRAULICS	AFNOR 48603 HV ISO VG 68 / 100

- New performance API CF-4 : deposits control around the rings increase engine protection and engine life time.
- New performance API CH-4 / ACEA E5 : outstanding dispersive properties, soot control avoid oil filter plugging during the complete drain interval.
- Anti-wear protection.
- A single lubricant to lubricate Engine / Transmissions (gearboxes and axles) / Wet brakes / and Hydraulic systems in order to avoid misuse or mixture.

RECOMMENDATIONS

Oil change : according to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J300	15W-40
Density at 20°C (68°F)	ASTM D1298	0.884
Viscosity at 40°C (104°F)	ASTM D445	94.4 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	13.5 mm ² /s
Viscosity index	ASTM D2270	139
Flash point	ASTM D92	234°C / 453°F
Drop point	ASTM D97	-33°C / -27°F
TBN	ASTM D 2896	11.0 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79. Web Site : www.motul.fr