



Timber 120

New formula, more adhesive

Lubricant for Power Chain Saws

Manual or Automatic Lubrication

TYPE OF USE

Specially formulated for Power Chain Saws Lubrication

All types of power chain saws with manual or automatic lubrication systems.

PERFORMANCE

Appropriate viscosity for an efficient lubrication while avoiding risks of oil splashes.

Fluid enough but highly adhesive.

Anti-oxidation and anti-rust.

Anti-corrosion and anti-wear.

ADVANTAGES

Reduction of oil consumption.

Reduction of heating.

Better protection for a lasting quality of the chains.

PROPERTIES

Density at 20°C (68°F)	ASTM D1298	0.874
Viscosity at 40°C (104°F)	ASTM D445	122.6 mm ² /s
Viscosity at 100°C (104°F)	ASTM D445	16.0 mm ² /s
Flash Point	ASTM D92	214°C / 417°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – Tel : 33 1 48 11 70 00 – FAX : 33 1 48 33 28 79 – Site Web : www.motul.fr