

SCHILLING - Aluminum gantry crane



The aluminium gantry crane. Heavy loads, easily moved.

A height- and length-adjustable crane system that offers maximum flexibility thanks to its variable adjustment options.

The SCHILLING aluminium gantry crane can be erected and dismantled in a very short time and with relatively little effort.

No structural modifications (e.g. dowel fastenings or similar) are necessary. Lightweight construction, with extremely high stability.

In the stationary version, the height of the four adjustable feet can be set individually and independently of each other and thus optimally adapted to the local conditions. Absolute stability for all load applications.

suspension point at the bolt of the trolley min. - max. in mm: 1730 - 2980

total height min.- max. in mm: 2175 - 3425

adjustment range of the beam support in mm : 850

adjustment range of the adjustment foot in mm : 400

total adjustment range in mm : 1250

total width of the crane max. in mm: 5277

distance between the lateral stands on the floor max. in mm: 4607

aluminium beam: separable alu single beam

Beam profile in mm: 220x60 - mit zusätzlich verstärkten Wandungen

total beam length in mm: 5164

usable beam length in mm: 4579
 length of the split beam parts in mm : 3000 / 2000
 Both pieces can be used as single beams
 The following combinations are possible:
 1. beam length in mm : 5000
 2. beam length in mm : 3000
 3. beam length in mm: 2000
 beam housing 1: sleeve 82x82 with bump stop
 beam housing 2: sleeve 82x82 with bump stop
 stand brace profile in mm: 80x60
 beam support profile in mm : 61x61
 length of the beam support 1 / 2 in mm: 1745 / 1495

Article no.	1321550-10
Execution	stationary
Height	medium
Load capacity	1500
Overall width	5277
Side frame distance bottom	4607
Overall height Min.	2175
Overall height Max.	3425
Max. height of hook-in	1730
Max. height of hook-in	2980
Lower edge of beam Min.	1808
Lower edge of beam Max.	3058
Total adjustment range	1250
Side frame weight left	30
Side frame weight right	29

Adjustment range of adjustable foot	400
Trestle strut profile	80x60
Beam support profile	61x61
Beam support adjustment range	850
Beam support length right	1495
Side frame width	1736
Horizontal adjuster Weight	4
Beam weight	81
Number of beams	single
Carrier version	separable
Carrier Article text	Partially or pluggable single beam
Carrier profile	220x60 - with additional reinforced walls
Carrier end left	Sleeve 82x82 with buffer stop
Carrier end right	Sleeve 82x82 with buffer stop
Beam profile Overall length	5000
Carrier profile length left	3000
Carrier profile length right	2000
Usable carrier length	4579
Overall beam length	5164
Weight of trolley	13

Total weight	157.0000
Carrier number	70011220605000-1-10
Carriage number	194215
Width of trolley	480

- [electric trolley - radio control](#)
- [electric trolley - direct](#)
- [Electric chain hoist - radio](#)
- [Pulley block made of aluminum](#)
- [Electric chain hoist](#)
- [Cabling, power supply](#)
- [circulating belt](#)
- [Manual winch for SCHILLING aluminum gantry crane](#)
- [Chassis for aluminum gantry crane](#)
- [Wall bracket for aluminum gantry crane](#)

SCHILLING Kran- und Hebetechnik GmbH
Ernst-Zimmermann-Straße 9-11
88045 Friedrichshafen
Germany

Tel.: +49 7541 60404-0
mail@schilling-fn.de

