

## SCHILLING - Aluminum gantry crane



The aluminum gantry crane. Movable even under load

The height and length adjustable crane system from SCHILLING – flexible and powerful and above all, with unrestricted mobility even under load, an invaluable advantage when it comes to the exact positioning of machines, for example. At rest when not in use, the rolling and swivelling movements can be blocked.

The SCHILLING aluminum gantry crane can be assembled and disassembled in a very short time and with relatively few manual operations. No structural modifications (e.g., dowel fastenings or similar) are necessary. Lightweight construction, with extremely high stability.

suspension point at the bolt of the trolley min. - max. in mm: 2135 - 2485

total height min.- max. in mm: 2235 - 2585

adjustment range of the beam support in mm : 350

adjustment range of the adjustment foot in mm : 0

total adjustment range in mm : 350

total width of the crane max. in mm: 5585

distance between the lateral stands on the floor max. in mm: 4393

aluminium beam: separable alu double beam

Beam profile in mm: 220x60

total beam length in mm: 5100

usable beam length in mm: 4399

length of the split beam parts in mm : 3000 / 2000

One of the two pieces (with sleeve) can be used as a single double beam.

The following combinations are possible:

1. beam length in mm : 5000
2. beam length in mm : 3000
3. beam length in mm: 2000

beam housing 1: sleeve 92x92 with bump stop and connection point for brace

beam housing 2: end piece

stand brace profile in mm: 120x80

beam support profile in mm : 81x81

length of the beam support 1 / 2 in mm: 1090 / 1090

number of wheels per lateral stand: 4x per lateral stand

- Steel casters
- Heavy-duty polyurethane lining
- With integrated caster and swivel head brake

When not in motion the rolling and swivel functions can be locked.

Article no.	14402050-10
Execution	movable under load
Height	small
Load capacity	2000
Overall width	5585
Side frame distance bottom	4393
Cross strut connection distance	4332
Overall height Min.	2235
Overall height Max.	2585
Max. height of hook-in	2135
Max. height of hook-in	2485
Lower edge of beam Min.	1868

Lower edge of beam Max.	2218
Total adjustment range	350
Side frame weight left	79
Side frame weight right	79
Number of wheels	4x per side frame
Trestle strut profile	120x80
Beam support profile	81x81
Beam support adjustment range	350
Beam support length right	1090
Seitengestelletiefe	596
Side frame width	1488
Aufsteckstutzen Gewicht	10
Horizontal adjuster Weight	23
Beam weight	119
Number of beams	twice
Carrier version	separable
Carrier Article text	Partially or pluggable double beam
Carrier profile	220x60
Träger Abstand	250
Carrier end left	Sleeve 92x92 with buffer stop und Querstrebenanschluss

Carrier end right	End strip
Beam profile Overall length	5000
Carrier profile length left	3000
Carrier profile length right	2000
Usable carrier length	4399
Overall beam length	5100
Weight of trolley	18
Total weight	347.0000
Carrier number	70034220605000-10
Carriage number	194122060
Width of trolley	480

- Two lateral stands, foldable with one height-adjustable beam support

grid dimension: 50 mm

- with 4 sheet steel swivel castors  
Heavy duty polyurethane tread with integrated wheel and swivel lock.

Wheel diameter: 200 mm

Wheel width: 50 mm

- The lateral stands can be folded up effortlessly and can therefore be stowed, stored, and transported in a space saving manner.
- One set of aluminium double beams  
The aluminium beam can be taken apart, e.g., for transport or storage purposes, and is therefore extremely space saving.  
The aluminium beam is relatively light, mobile, quick, and easy to assemble (a set consists of two single beams).  
Separable resp. pluggable aluminium beam.
- One overhead lockable trolley

The trolley is used to hold the chain hoist or alternatively the lifting straps.  
Due to the overhead trolley, the maximum lift can be used in relation to the total height.

Even under full load, the trolley is infinitely adjustable and can be locked in any position.

- Four bump stops  
As collision protection for the trolley
- One beam mounting  
This fixes the two aluminium supports in exact parallelism.
- One integrated horizontal adjuster  
Through the use of the horizontal adjuster the usable length of the aluminium Gantry Crane can be adjusted smoothly between the two lateral stands.  
The running track width of the aluminium beam is variable.  
This guarantees a higher level of flexibility for the user.

---

SCHILLING Kran- und Hebertechnik GmbH  
Ernst-Zimmermann-Straße 9-11  
88045 Friedrichshafen  
Germany

Tel.: +49 7541 60404-0  
[mail@schilling-fn.de](mailto:mail@schilling-fn.de)