

## SCHILLING - Aluminum gantry crane



The aluminium gantry crane. Heavy loads, easily moved.

A height- and length-adjustable crane system that offers maximum flexibility thanks to its variable adjustment options.

The SCHILLING aluminium gantry crane can be erected and dismantled in a very short time and with relatively little effort.

No structural modifications (e.g. dowel fastenings or similar) are necessary. Lightweight construction, with extremely high stability.

In the stationary version, the height of the four adjustable feet can be set individually and independently of each other and thus optimally adapted to the local conditions. Absolute stability for all load applications.

suspension point at the bolt of the trolley min. - max. in mm: 2310 - 4010

total height min.- max. in mm: 2755 - 4455

adjustment range of the beam support in mm : 1300

adjustment range of the adjustment foot in mm : 400

total adjustment range in mm : 1700

total width of the crane max. in mm: 8234

distance between the lateral stands on the floor max. in mm: 7753

aluminium beam: separable alu single beam

Beam profile in mm: 220x60 - mit zusätzlich verstärkten Wandungen

total beam length in mm: 8100

usable beam length in mm: 7479

length of the split beam parts in mm : 4000 / 4000

One of the two pieces (with sleeve) can be used as a single beam.

The following combinations are possible:

1. beam length in mm : 8000

2. beam length in mm : 4000

beam housing 1: sleeve 92x92 with bump stop

beam housing 2: end piece

stand brace profile in mm: 100x70

beam support profile in mm : 71x71

length of the beam support 1 / 2 in mm: 2355 / 2105

Article no.	1331080-10
Execution	stationary
Height	high
Load capacity	1000
Overall width	8234
Side frame distance bottom	7753
Overall height Min.	2755
Overall height Max.	4455
Max. height of hook-in	2310
Max. height of hook-in	4010
Lower edge of beam Min.	2388
Lower edge of beam Max.	4088
Total adjustment range	1700
Side frame weight left	52
Side frame weight right	50

Adjustment range of adjustable foot	400
Trestle strut profile	100x70
Beam support profile	71x71
Beam support adjustment range	1300
Beam support length right	2105
Side frame width	2238
Horizontal adjuster Weight	11
Beam weight	119
Number of beams	single
Carrier version	separable
Carrier Article text	Partially or pluggable single beam
Carrier profile	220x60 - with additional reinforced walls
Carrier end left	Sleeve 92x92 with buffer stop
Carrier end right	End strip
Beam profile Overall length	8000
Carrier profile length left	4000
Carrier profile length right	4000
Usable carrier length	7479
Overall beam length	8100
Weight of trolley	13

Total weight	247.0000
Carrier number	70024220608000-1-10
Carriage number	194315
Width of trolley	480

- Two lateral stands, foldable with height-adjustable beam support

grid dimension: 50 mm

- with two height adjustable adjustment feet

grid dimension: 40 mm

The lateral stands can be folded up effortlessly and can therefore be stowed, stored, and transported in a space saving manner.

- One aluminium beam  
Separable resp. pluggable aluminium beam.
- One fixable park brake trolley  
The trolley is used to hold the chain hoist or alternatively the lifting straps. Even under full load, the trolley is infinitely adjustable and can be locked in any position.
- Two bump stops  
As collision protection for the trolley
- One integrated horizontal adjuster  
Through the use of the horizontal adjuster the usable length of the aluminium Gantry Crane can be adjusted smoothly between the two lateral stands.

</MTMzMTA4MC0xMA/downloads/1331080-001.idw.pdf>

</MTMzMTA4MC0xMA/downloads/1331080-001.stp>

88045 Friedrichshafen  
Germany

Tel.: +49 7541 60404-0  
[mail@schilling-fn.de](mailto:mail@schilling-fn.de)