

## SCHILLING - Aluminum gantry crane



The aluminum gantry crane. Movable even under load

The height and length adjustable crane system from SCHILLING – flexible and powerful and above all, with unrestricted mobility even under load, an invaluable advantage when it comes to the exact positioning of machines, for example. At rest when not in use, the rolling and swivelling movements can be blocked.

The SCHILLING aluminum gantry crane can be assembled and disassembled in a very short time and with relatively few manual operations. No structural modifications (e.g., dowel fastenings or similar) are necessary. Lightweight construction, with extremely high stability.

suspension point at the bolt of the trolley min. - max. in mm: 3003 - 4153

total height min.- max. in mm: 3104 - 4254

adjustment range of the beam support in mm : 1150

adjustment range of the adjustment foot in mm : 0

total adjustment range in mm : 1150

total width of the crane max. in mm: 7585

distance between the lateral stands on the floor max. in mm: 6393

aluminium beam: separable alu double beam

Beam profile in mm: 220x60

total beam length in mm: 7100

usable beam length in mm: 6399

length of the split beam parts in mm : 4000 / 3000

One of the two pieces (with sleeve) can be used as a single double beam.

The following combinations are possible:

1. beam length in mm : 7000
2. beam length in mm : 4000
3. beam length in mm: 3000

beam housing 1: sleeve 92x92 with bump stop and connection point for brace

beam housing 2: end piece

stand brace profile in mm: 120x80

beam support profile in mm : 81x81

length of the beam support 1 / 2 in mm: 2045 / 2045

number of wheels per lateral stand: 4x per lateral stand

- Steel casters
- Heavy-duty polyurethane lining
- With integrated caster and swivel head brake

When not in motion the rolling and swivel functions can be locked.

Article no.	14601070-10
Execution	movable under load
Height	high
Load capacity	1000
Overall width	7585
Side frame distance bottom	6393
Cross strut connection distance	6332
Overall height Min.	3104
Overall height Max.	4254
Max. height of hook-in	3003
Max. height of hook-in	4153
Lower edge of beam Min.	2736

Lower edge of beam Max.	3886
Total adjustment range	1150
Side frame weight left	104
Side frame weight right	104
Number of wheels	4x per side frame
Trestle strut profile	120x80
Beam support profile	81x81
Beam support adjustment range	1150
Beam support length right	2045
Seitengestelltiefe	596
Side frame width	2312
Aufsteckstutzen Gewicht	10
Horizontal adjuster Weight	23
Beam weight	153
Number of beams	twice
Carrier version	separable
Carrier Article text	Partially or pluggable double beam
Carrier profile	220x60
Träger Abstand	250
Carrier end left	Sleeve 92x92 with buffer stop und Querstrebenanschluss

Carrier end right	End strip
Beam profile Overall length	7000
Carrier profile length left	4000
Carrier profile length right	3000
Usable carrier length	6399
Overall beam length	7100
Weight of trolley	18
Total weight	440.0000
Carrier number	70034220607000-10
Carriage number	194322060
Width of trolley	480

- Two lateral stands, foldable with one height-adjustable beam support

grid dimension: 50 mm

- with 4 sheet steel swivel castors  
Heavy duty polyurethane tread with integrated wheel and swivel lock.

Wheel diameter: 200 mm

Wheel width: 50 mm

- The lateral stands can be folded up effortlessly and can therefore be stowed, stored, and transported in a space saving manner.
- One set of aluminium double beams  
The aluminium beam can be taken apart, e.g., for transport or storage purposes, and is therefore extremely space saving.  
The aluminium beam is relatively light, mobile, quick, and easy to assemble (a set consists of two single beams).  
Separable resp. pluggable aluminium beam.
- One overhead lockable trolley

The trolley is used to hold the chain hoist or alternatively the lifting straps.  
Due to the overhead trolley, the maximum lift can be used in relation to the total height.

Even under full load, the trolley is infinitely adjustable and can be locked in any position.

- Four bump stops  
As collision protection for the trolley
- One beam mounting  
This fixes the two aluminium supports in exact parallelism.
- One integrated horizontal adjuster  
Through the use of the horizontal adjuster the usable length of the aluminium Gantry Crane can be adjusted smoothly between the two lateral stands.  
The running track width of the aluminium beam is variable.  
This guarantees a higher level of flexibility for the user.

---

SCHILLING Kran- und Hebetchnik GmbH  
Ernst-Zimmermann-Straße 9-11  
88045 Friedrichshafen  
Germany

Tel.: +49 7541 60404-0  
[mail@schilling-fn.de](mailto:mail@schilling-fn.de)