



Strong and durable, Reicrop protects crops from pests, cold temperatures, and winds.

Our Reicrop products offer a wide range of crop cover solutions that excel in a variety of applications and environments. Reicrop is recommended for crops such as melons, green/red peppers, cucumbers, watermelon, leaks, and endives.

Features & Benefits

- Available in a wide range of widths and weights from 17gsm - 30gsm
- It incorporates a strip of lateral reinforcement
- Easy and reliable installation
- UV treated



Protection against cold temperatures and strong wind



Insect protection



Permits filtration of more than 80% of the sun's rays



Improved yield and crop quality



Grow your crops up to 5°C degrees warmer than the exterior temperature

Solutions to enhance crop growth and protection

Our industry knowledge help ensure the greatest performance in the field when using our agriculture products.

Product Range	Unit	Target	Min.	Max.	Test Method
17 g/m² REICROP Glued®					
Weight	(g/m ²)	17	15	19	WSP 130.1 (05)
TS at peak MD	(N/50mm)	39	19	-	WSP 110.4 (05)
EL at peak MD	(%)	127	75	170	WSP 110.4 (05)
TS at peak CD	(N/50mm)	21	12	-	WSP 110.4 (05)
EL at peak CD	(%)	122	69	175	WSP 110.4 (05)
Adhesive break	(N/50mm)	24	13	35	WSP 110.4 (05) (ERT 20.2-89)
Non-woven break	(N/50mm)	21	11.8	30.2	WSP 110.4 (05) (ERT 20.2-89)
19 g/m² REICROP Glued®					
Weight	(g/m ²)	19	17	21	WSP 130.1 (05)
TS at peak MD	(N/50mm)	42	22	-	WSP 110.4 (05)
EL at peak MD	(%)	117	65	170	WSP 110.4 (05)
TS at peak CD	(N/50mm)	23	13	-	WSP 110.4 (05)
EL at peak CD	(%)	115	62	168	WSP 110.4 (05)
Adhesive break	(N/50mm)	26	13	39	WSP 110.4 (05) (ERT 20.2-89)
Non-woven break	(N/50mm)	24	12.5	35.5	WSP 110.4 (05) (ERT 20.2-89)
23 g/m² REICROP Glued®					
Weight	(g/m ²)	23	21	25	WSP 130.1 (05)
TS at peak MD	(N/50mm)	51	30	-	WSP 110.4 (05)
EL at peak MD	(%)	143	94	192	WSP 110.4 (05)
TS at peak CD	(N/50mm)	29	19	-	WSP 110.4 (05)
EL at peak CD	(%)	135	94	176	WSP 110.4 (05)
Adhesive break	(N/50mm)	26	13	39	WSP 110.4 (05) (ERT 20.2-89)
Non-woven break	(N/50mm)	24	12.5	35.5	WSP 110.4 (05) (ERT 20.2-89)
30 g/m² REICROP Glued®					
Weight	(g/m ²)	30	27	33	WSP 130.1 (05)
TS at peak MD	(N/50mm)	73	48	-	WSP 110.4 (05)
EL at peak MD	(%)	137	90	190	WSP 110.4 (05)
TS at peak CD	(N/50mm)	41	23	-	WSP 110.4 (05)
EL at peak CD	(%)	132	69	195	WSP 110.4 (05)
Adhesive break	(N/50mm)	42	17	67	WSP 110.4 (05) (ERT 20.2-89)
Non-woven break	(N/50mm)	39	15.9	62.1	WSP 110.4 (05) (ERT 20.2-89)

Note:

The specification are based ± 2

Exceptions to the norms:

Basis Weight: We analyze samples of 100cm²

TS: Tensile Strength / EL: Elongation - The distance between clamps is 100mm

MD: Machine direction / CD: Cross direction

To make us a part of your agriculture process, please contact us at: euhqagriculture@berryglobal.com

agriculturecovers.com

