

North Fork Reloading Data

300 H&H Magnum



Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs of excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Winchester m70

Barrel length: 26" (66cm)

Primer: CCI 250

Case: Winchester

North Fork Semi Spitzer (SS)

Bullet diameter: .308"

Max COL: 3.6" (91,4mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
150	IMR 4350	70	3 280	1 000	72	3 415	1 041
150	H-4831	76	3 271	997	77	3 375	1 029
150	IMR 4831	72	3 215	980	74	3 285	1 002
165	IMR 4350	67	3 100	945	69	3 215	980
165	H-4831	73	3 200	976	74	3 220	982
180	IMR 4350	66	3 000	915	68.5	3 100	945
180	IMR 4831	69	2 980	909	71	3 125	953
180	H-4831	71	3 025	922	73	3 095	944
200	IMR 4350	64	2 950	899	66	3 000	915