

North Fork Reloading Data

300 Remington Ultra Magnum



Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs off excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Remington 700 CDL

Barrel length: 26" (66cm)

Primer: CCI 250

Case: Remington

North Fork Semi Spitzer (SS)

Bullet diameter: .308"

Max COL: 3.6" (91,4mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
150	MagPro	91.1			99	3 380	1 030
150	4000-MR	83.7			91	3 331	1 015
150	Re25	89.7			97.5	3 359	1 024
150	RS Magnum	93.8			102	3 389	1 033
165	Re25	86.9			94.5	3 260	994
165	H1000	89.7			97.5	3 267	996
165	IMR 7828	84.6			92	3 303	1 007
165	N570	94.8			103	3 354	1 022
180	Re25	84.6			92	3 176	968
180	Retumbo	91.1			99	3 218	981
180	H870	94.8			103	3 212	979
180	N570	92.0			100	3 273	998
200	Re25	81.9			89	3 018	920
200	Retumbo	87.9			95.5	3 054	931
200	RS Magnum	85.1			92.5	3 037	926
200	N570	88.8			96.5	3 113	949