

North Fork Reloading Data



338 RCM

Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs off excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Ruger m77 Hawkeye

Barrel length: 20" (51cm)

Primer: CCI Magnum

Case: Hornady

North Fork Semi Spitzer (SS)

Bullet diameter: .338"

Max COL: 2.845" (72,3mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
225	Reloader 15	52.4			57	2 685	818
225	H414	56.1			61	2 660	811
225	H4350	56.1			61	2 650	808
225	IMR4895	49.7			54	2 600	792
250	H414	55.2			60	2 580	786
250	H4350	50.6			55	2 390	728
250	IMR4895	50.1			54.5	2 345	715