

North Fork Reloading Data

338 Winchester Magnum



Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs of excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Winchester m70

Barrel length: 26" (66cm)

Primer: Federal 215

Case: Remington

North Fork Semi Spitzer (SS)

Bullet diameter: .338"

Max COL: 3.34" (84,5mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
200	Reloader 19	70	2 700	823	75	2 900	884
200	H4831SC	72	2 650	808	74	2 850	869
200	H4350	68			74	2 950	899
225	Reloader 19	70	2 750	838	74	2 859	872
225	H4350	67	2 640	805	70	2 880	878
225	Reloader 17	68	2 825	861	69.5	2 860	872
225	H414	61.5			67	2 785	849
240	H4831SC	69	2 550	777	73	2 737	834
240	H4350	64			69.5	2 715	828
240	Reloader 17	62	2 524	770	67.5	2 782	848
250	Reloader 19	70	2 700	823	75	2 900	884