

North Fork Reloading Data



375 Ruger

Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs off excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Ruger Hawkeye African

Barrel length: 23" (58.5cm)

Primer: CCI 250

Case:

North Fork Flat Point (FP)

Bullet diameter: .375"

Max COL: 3.340" (84,8mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
250	H414	78.7			85.5	3 000	914
250	RE15	71.8			78	2 928	892
270	Varget	68.1			74	2 700	823
270	IMR 4895	68.1			74	2 700	823
300	H414	71.8			78	2 650	808
300	IMR 4895	64.4			70	2 625	800
350	H4350	65.3			71	2 350	716
350	H414	65.8			71.5	2 300	701

North Fork Cup Point Solid (CPS)

Bullet diameter: .458"

Max COL: 2.505" (63,6mm)

<i>Bullet Weight (gr)</i>	<i>Powder</i>	<i>Minimum Charge (gr)</i>	<i>Velocity (FPS)</i>	<i>Velocity (M/S)</i>	<i>Maximum Charge (gr)</i>	<i>Velocity (FPS)</i>	<i>Velocity (M/S)</i>
350	H4198	45	1 954	596	47	2 053	626
350	RE-7	47	1 925	587	49	2 041	622