

North Fork Reloading Data



416 Remington Magnum

Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs off excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Winchester m70

Barrel length: 24" (61cm)

Primer: Federal 215

Case: Remington

North Fork Semi Spitzer (SS)

Bullet diameter: .416"

Max COL: 3.59" (91,2mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
370	Re15	74	2 415	736	81.5	2 625	800
400	Re15	73	2 250	686	80	2 450	747

North Fork Flat Point Solid / Cup Point Solid (FPS/CPS)

Bullet diameter: .416"

Max COL: 3.59" (91,2mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
430	Varget	65.3			71	2 260	689
430	H-4895	64.4			70	2 230	680
430	RE17	72.7			79	2 300	701