

North Fork Reloading Data



416 Rigby

Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs off excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Winchester m70

Barrel length: 24" (61cm)

Primer: Federal 215

Case: Norma

North Fork Semi Spitzer (SS)

Bullet diameter: .416"

Max COL: 3.75" (95,25mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
400	Re 22	89.2			97	2432	741
400	H4831SC	94.8			103	2500	762
400	IMR 4350	85.6			93	2558	780

North Fork Flat Point Solid / Cup Point Solid (FPS/CPS)

Bullet diameter: .416"

Max COL: 3.75" (95,25mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
400	AA MagPro	93.8			102	2435	742
400	H4350	87.4			95	2601	793