

North Fork Reloading Data

45-70 Government



Safety information when handloading

North Fork disclaims all liability for any damages which may result from handloading since individual handloading procedures are beyond our control. Handloading may only be performed by qualified adults. Careless or incorrect handloading can result in severe personal injury or even death. Handloading should only be performed after thorough instruction. Our stated loads are only examples of loads that we have tried in our own rifles. *Always reference officially published data from powder manufacturers and start off using starting loads, step loads up carefully and conservatively. Reduce loads at the first signs of excessive pressure. North Fork recommends that all handloaders use a chronograph.*

Test firearm: Marlin Guide Gun

Barrel length: 18" (45.7cm)

Primer: CCI 200

Case: Winchester

North Fork Flat Point (FP)

Bullet diameter: .458"

Max COL: 2.580" (65,5mm)

Bullet Weight (gr)	Powder	Minimum Charge (gr)	Velocity (FPS)	Velocity (M/S)	Maximum Charge (gr)	Velocity (FPS)	Velocity (M/S)
350	H419	45	1 875	571	51.5	2 160	658
350	H322	51	1 890	576	57	2 160	658
350	IMR-4198	43	1 875	571	49.5	2 150	655
350	RE-7	51	2 000	610	57	2 220	677
350	RE-10	53.5	2 060	628	57	2 190	668
350	Benchmark	53	1 900	579	60	2 190	668
350	VV N-130	51.5	2 050	625	55.5	2 210	674
350	VV N-133	55	2 000	610	57	2 100	640
350	AA 2230	57	1 920	585	59	2 120	646
350	H335	55	1 900	579	65	2 180	664

North Fork Cup Point Solid (CPS)

Bullet diameter: .458"

Max COL: 2.505" (63,6mm)

<i>Bullet Weight (gr)</i>	<i>Powder</i>	<i>Minimum Charge (gr)</i>	<i>Velocity (FPS)</i>	<i>Velocity (M/S)</i>	<i>Maximum Charge (gr)</i>	<i>Velocity (FPS)</i>	<i>Velocity (M/S)</i>
350	H4198	45	1 954	596	47	2 053	626
350	RE-7	47	1 925	587	49	2 041	622